	WATER WE	LL RECORD	Form	WWC-5	KSA	82a-12 ⁻	12					
1 LOCATION OF WATER WELL:				SECTION NUMBE						RANGE NUMBER		
Sedgwick	SE 1/4		SE 1/4	14		т 2	<u>6</u> S	R	1E	E/W		
Distance and direction from nearest town or city 5912 E. 53rd St. N.		· ·	_									
	FENBAUGH (k City, Kansas										
	N. 143rd St. E		1011				Board of Ag	riculture, Divisio	n of Wat	er Resource		
	nita, Kansas	·•		ZIP COI	DE: 67228	3	Application Nu	ımber:				
	DEPTH OF COMPL	ETED WELL:	116	ft.		VATION:						
WITH AN "X" IN SECTION BOX:	pth of groundwater E			ft.			ft.			ft.		
	ELL'S STATIC WAT	_	5 FT		ND SURFAC	CE MEASI	JRED ON mo.	/day/yr·	8/19/0			
NW NE			ell water wa			ft. after		rs of pumping		gpm		
	Est. Yield:	•	ell water wa			ft. after		rs of pumping	_	gpm		
₩ w E B	ore Hole Diameter	12 in.		to 116	ft.	and	in.	1	to	ft.		
	ELL WATER TO BE						9. Dewater	ring ¹¹ .	Injecti	on well		
				pply 🔨			مريا 10. Monitor		er (Spe	cify below)		
	 Irrigation 4. In Vas a chemical/bacterio 	ndustrial 6. Oil f			ur conaitioi ES (NO		, what mo/day	/yr wa	s sample		
_	bmitted	> Sogical calliple sacrime	too to Dopara		Was Water		fected?	YES	NC)		
5 TYPE OF CASING USED:	5. Wrought Ir	ron 7. Fiber	rolass	9. Other (S	specify below	v) CAS	SING JOINTS:	Glued	Ţ	hreaded		
1. Steel 3. RPM (SF	۲)		·	SDR-26				Welded	(Clamped		
2. PVC 4. ABS	6. Asbestos-		crete tile									
Blank casing diameter 5	_	30 ft., Di			0	ft.,	Dia.	in. to)	ft.		
Casing height above land surface:	12 in.,	Weigh	it: 2.3 5	lbs. / ft.	. *	Wall th	nickness or gau	uge No.	214			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)												
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)												
		0. 1	(0,1,	10.71000010	oo oomon	, _ , , , ,	5.10 0000 (opo.					
SCREEN OR PERFORATION OPENING 1. Continuous slot 3. Mill sl		auzed wrapped		7. Torch cu	ıŧ	9 Dril	led holes	11. Nor	ne (ope	en hole)		
		• •		8. Saw cut	_				.о (ор			
2. Louvered shutter 4. Key p	unched o. w	ire wrapped				10. Oth	er (specify)					
SCREEN - PERFORATION INTERVAL	From	30 ft.	to 1	16 ft.,	F	rom	ft.	to)	ft.		
	From	ft.	to	ft.,	F	rom	ft.	to)	ft.		
GRAVEL PACK INTERVALS:	From	24 ft.	to]	16 ft.,	F	rom	ft.	to)	ft.		
	From	ft.	to	ft.,	′ F	rom	ft.	to)	ft.		
6 GROUT MATERIALS: 1. Neat	cement	2. Cement Grout	t	3. Ben	tonite		Other ben	tonite hole	e plug	ŗ		
Grout Intervals: From 4	ft. to	24 ft., F	rom	ft.	to	ft.,	From	ft.	to	ft.		
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy			10. Liv	0. Livestock pens			13. Insecticide storage 15. Oil well/Gas well					
9 Source larger 11 Fuel storage 44 Abandon materials						16. Othe	16. Other (specify below)					
		Feed yard		rtilizer stora				•				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12 Direction from well? East							How many feet? 100 ft. plus					
	LITHOLOGIC	LOG	Fr	om T	o l			OGIĆ LO	3			
0 3 topsoil		·										
3 9 clay												
9 12 fine sand 12 116 gray shale												
12 116 gray shale												
					·							
								 				
												
Contractor's or Landowner's Certifi		vell was 1. consti	ructed	2. reconst	ructed o	r 3.	plugged	under my jur	isdictio	n and		
was completed on (mo/day/year) 8/19/2008 and this record is true to the best of my knowledge and belief.												
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/22/2008												
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb												

Todd S. Harp