	WATER WELL	RECORD F	orm WV	/C-5 K	SA 82a-1212	2			
1 LOCATION OF WATER WELL:	FRACTION SE 1/4 S	W NIE	1	TION NUMBER			RANGE NUM		
Sedgwick  Distance and direction from nearest town or city		17.1	1/4	29	Т 26	S	R 1E	E/W	
42nd St and Dale Wichita, Kansas (7 wells on 1 permit)									
2 WATER WELL OWNER: WICHITA, CITY OF  Board of Agriculture, Division of Water Resource									
	N. Main hita, Kansas			D CODE.		Application Num	20070		
	DEPTH OF COMPLETE	ED WELL: 4		P CODE:	ELEVATION:	Application Num	iber: 20070		
WITH AN "X" IN SECTION BOX:	epth of groundwater Enc		ft.			ft.		ft.	
	VELL'S STATIC WATER		FT. BELO	W LAND SU	RFACE MEASUR	RED ON mo/d	ay/yr: 8/8/0	8	
NWNE	Pump te	est data: Well wa	ter was		ft. after	hours	of pumping @	gpm	
W X E	•	gpm Well wa			ft. after		of pumping @	gpm	
	Bore Hole Diameter /ELL WATER TO BE US	12 in.	to 4	10 ft.	and	in.	to	ft. ion well	
	5. Dewatering								
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
	Was a chemical/bacteriologic ubmitted	cal sample submitted to I	Department?	<b>YES</b> Was W	/ater Well Disinfe		YES NO		
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded									
1. Steel 3. RPM (SR) Welded Clamped									
2. PVC 4. ABS Blank casing diameter 8	in. to 20		ile .		<b>"</b>	ia. i		ft.	
	10	,	in.	to	,		in. to	II.	
Casing height above land surface: 12 in., Weight: 5.52 lbs. / ft. Wall thickness or gauge No332  TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole							en hole)		
2. Louvered shutter 4. Key	punched 6. Wire	wrapped	(8. Sa	w cut	10. Other	(specify)			
SCREEN - PERFORATION INTERVAL	From 2	<b>20</b> ft. to	40	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From 2	20 ft. to		ft.,	From	ft.	to	ft.	
	From	ft. to	)	ft.,	From	ft.	to	ft.	
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug  Grout Intervals: From 0 ft. to 20 ft. From ft to ft From ft to ft							-		
What is the nearest source of possible contamination:						ft.			
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well									
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify beld a water well 19. Severage None Apparent						•			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12 Direction from well?			12. Fertilize	r storage	How many feet?				
From To	LITHOLOGIC LO	OG	From	To	TIOW MAI		GIC LOG		
0 3 topsoil									
3 8 clay 8 12 sandy clay			<del>                                     </del>	<del>                                     </del>					
12 40 medium san	d						1		
	1000								
	-0.4			<del>   </del>					
				<del>  </del>					
	7917								
				<del>                                     </del>					
7 Contractor's or Landowner's Certi	fication: This water well	was 1 Constructor	) 2 ra	constructed	or 3. <b>p</b>	lugged	under my jurisdictio	n and	
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 8/8/2008 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236  This water well record was completed on (mo/day/year)  8/11/2008									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									