	WATER WELL R	ECORD F	orm WW	C-5 K	SA 82a-1212	2		
1 LOCATION OF WATER WELL:			1	SECTION NUMBER TOWNSHI				
Sedgwick Distance and direction from nearest town or city	NE 1/4 NE	1/4 NE	1/4	35	Т 26	S	R 11	C E/W
·	Wichita, Kansas	within city?						
	KS, John Dr.							
RR#,ST. ADDRESS,BOX #: 3715 N. Oliver								
	hita, Kansas			CODE:		Application Num	ber:	
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPLETED	WELL: 38	ft.		ELEVATION:	grade		
N De	pth of groundwater Encoun	tered:	ft.			ft.		ft.
	ELL'S STATIC WATER LE			W LAND SU	JRFACE MEASUF		• •	/08
NWNE	Pump test d				ft. after		of pumping @	gpm
₩ W E B	Est. Yield: gpm Bore Hole Diameter	n Well wate in.	er was to	ft.	ft. after and	nours in.	of pumping @ to	gpm ft.
	ELL WATER UMS E USED		10	16.	Bild	9. Dewaterii	44 1-1-	ction well
. i i i	1. Domestic 3. Feedlot		er supply	7. Lawn a	and garden only	J. Dewatern	.8	pecify below
	2. Irrigation 4. Industri				ditioning		g well aband	
· ·	Was a chemical/bacteriological s ubmitted	sample submitted to D	epartment?	YES Was V	NO Vater Well Disinfe		vhat mo/day/yr v	vas sample NO
5 TYPE OF CASING USED:		7 51	9 01	her (Specify		NG JOINTS:	Glued	Threaded
1. Steel 3. RPM (SI	R) 5. Wrought Iron	7. Fiberglass		ner (opecity	below) Onon	10 00,1110.	Welded	Clamped
2. PVC 4. ABS	6. Asbestos-Cemen	t 8. Concrete til	е					·
Blank casing diameter 8	in. to f	ft., Dia.	in.	to	ft., D	ia. i	in. to	ft.
Casing height be W and surface:	36 in.,	Weight:	lb	s. / ft.	Wall thic	kness or gaug	ge No.	
TYPE OF SCREEN OR PERFORATION		7 DVC	0.41	20	11 Oth	or (enocify) N	J/A	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A								
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)								
								opon 11010,
2. Louvered shutter 4. Key p	ounched 6. Wire wra	apped	8. \$a \	w cut	10. Other	(specify) N	A	
SCREEN - PERFORATION INTERVAL	From	ft. to		ft.,	From	ft.	to	ft.
	From ^	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	ft. to		ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug							_	
Grout Intervals: From ft. to ft., From ft. to ft., From 3 ft. to 24 What is the nearest source of possible contamination:							24 ft.	
				Livestock pens 13. Insecticide storage 15. Oil well/Gas well				
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify be						pecify below)		
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well? East					How mar	ny feet? 250		
From To	LITHOLOGIC LOG	}	From 0	То			GIC LOG	
				3	natural earth backfill bentonite hole plug			
			24	24 38	chlorinated s		ravel	
						min man e		
							······································	······
Contractor's or Landowner's Certification: This water well was 1, constructed 2, reconstructed or 3, plugged under my jurisdiction and								
was completed on (mo/day/year) 8/4/2008 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's Licer	nse No. 236	This water we	ell record wa	s completed	d on (mo/day/year	8/7/	/2008	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp								
	•				, (· ICOUIT	,