1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER TOWNSHIP NUMB
S IN ID LAW
Distance and direction from nearest town or city street address of well if located within city?
6136 N. Fairfield Ave. Wichita, Kansas
2 WATER WELL OWNER: BOWER, David
RR#,ST. ADDRESS,BOX #: 6136 N. Fairfield Ave. Board of Agriculture, Division of Water Resource
CITY, STATE: Wichita, Kansas ZIP CODE: Application Number:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 45 ft. ELEVATION: WITH AN "X" IN SECTION BOX:
N Depth of groundwater Encountered: ft. ft. ft. ft. well's STATIC WATER LEVEL 8 FT BELOW LAND SURFACE MEASURED ON mor/day/yr: 4/25/09
District Act data Mall materials and a first minday, yi.
9
E Bore Hole Diameter 12 in. to 45 ft. and in. to ft
WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well 1. Domestic 3. Feedlot 5. Public water supply 12. Cher (Specify hole)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample
submitted Was Water Well Disinfected? YES NO TYPE OF CASING USED: 5 Wrought Iron 7 Fiberolass 9. Other (Specify below) CASING JOINTS: Glued Threaded
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS.
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-20
Blank casing diameter 5 in. to 35 ft., Dia. in. to ft., Dia. in. to ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)
SCREEN - PERFORATION INTERVAL From 35 ft. to 45 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 24 ft. to 45 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft., F
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage
Direction from well? East How many feet? 50 ft. plus
0 3 topsoil
3 7 clay
7 12 sandy clay
25 44 medium sand
44 45 clay
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 4/25/2009 and this record is true to the best of my knowledge and belief
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/27/2009
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp