		ATER WELL	RECORD FO	orm vvvvC-5	KSA 82a-	1212 ID No			
1 LOCATION OF WATER WELL:				I .	tion Number	r Township	Number	Range Number	
county: Sedgwick	NW			1/4	35	⊤ 2 €	S S	R 1	Ε
stance and direction from nearest			vell if located	within city?					
pproximately 100' E of EW									
WATER WELL OWNER: Kocl									
R#, St. Address, Box # : 4111						Board of Ad	griculture, Divisio	n of Water Res	ources
ity, State, ZIP Code : Wich	nita, KS 672	220				Application			
LOCATE WELL'S LOCATON WIT	TH 4			4.0					
AN "X" IN SECTION BOX:		OF COMPLET	ED WELL	18	ft. ELE	:VATION:			
	Depth(s) Gro	oundwater End	countered 1	10	6 1	ft. 2	ft. 3		ft.
NWNE	WELL'S STA	ATIC WATER	LEVEL	ft.	below land	surface measure	ed on mo/day/yr		
	F	Pump test data	a: Well wate	r was		ft. after	hours pum	ping	gpm
W X	E Est. Yield	gpm	: Well wate	r was		ft. after	hours pum	ping	gpm
	Bore Hole D	iameter '	12 in. to	20)	ft, and	7 in to	22.5	fŧ
SWSE	WELL WATE	ER TO BE US	EDAS: 5 P	ublic water s	upply	8 Air condi	itioning 11 <u>l</u>	njection well	
	1 Dom	estic 3 Fee	d lot 6 C	il field water	supply	9 Dewater	ing 12 (Other (Specify	below)
S							ring well E		
3							X If yes, mo		
	submitted						cted? Yes		
TYPE OF BLANK CASING USED):	5 Wro	ought Iron	8 Concr			OINTS: Glued		
1 Steel 3 RM			estos-Cemen		(specify hel	ow)	Welded	Olampe	٠
2 PVC 4 ABS		7 Fibe			()	···,	Threaded	Flus	<u> </u>
lank casing diameter 4		2 4	•		10.20	·			
talia balah abau landa ufa	Stick up	π.,	Dia 😁	n. troi	m 10-20	tt., Dia	1* in.	to 8 *	ft.
asing height above land surface YPE OF SCREEN OR PERFORAT		in., weigh	ıt				or gauge No.	SCH. 4	Ŭ.
					PVC		sbestos-cement		
1 Steel 3 Sta 2 Brass 4 Gal	inless steel vanized steel	5 Fibe	erglass	8	RMP (SR)	11 0	ther (specify)		
Z DIASS 4 GAI CREEN OR PERFORATION OPEN		6 Cor		9 ed wrapped	ABS	12 N	one used (open h	nole)	
	3 Mill slot			wrapped wrapped		8 Saw cut Drilled hol	11	None (open h	iole)
	4 Key punched		7 Torch			10 Other (sp	ecify)		
CREEN-PERFORATED INTERVAL	• •		ft. to	18	ft	From 8	3* ft. to	18*	
	From		ft to		: ^(*)	From	ft. to		· IL.
GRAVEL PACK INTERVALS		6	ft. to	20		From	4.40		ا ۱۱۰۰
				· · · · · · · · · · · · · · · · · · ·		From	ft. to		
GROUT MATERIAL: 1 Ne		**		0.5			ft. to		ft.
_	at cement				tonite	4 Other			
Grout Intervals From 3	tt. to	D ft. Fr	om 4	U ft. 1		5 ft. From	١		
What is the nearest source of possible						stock pens		oned water wel	11
1 Septic tank	4 Lateral lin		7 Pit privy		11 Fuel			ll/ Gas well	
2 Sewer lines	5 Cess poo		8 Sewage			lizer storage	16 Other	(specify below)	ļ
3 Watertight sewer lines	6 Seepage	pit	9 Feedyar	ď		cticide storage			
Pirection from well? FROM TO CODE	LIT	HOLOGIC LO		FROM	How many				
	Silty Clay, ы		<u> </u>	FROM	ТО	<u> </u>	PLUGGING INTE	RVALS	
	Clay, red brov			-					
	Sandy Clay,								
	Clay, red brov			 		*1" casing	attached to	outside of	4"
	rained sand	,, , .				casing	unaonica to	outside of	7
	Clayey Sand	, red brown	, fine to						
	nedium graine								
	Silty Clay, br								
	Sand, coarse								
	nterbedded		y and			_			
	Sand, red bro				1				
1/11 18/11 18	Sand, coarse	grained, trad	ce gravel						
	Shale, olive g	ray, weather		(4)					

under the business name of Geotechnical Services Inc.

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.