1 LOCATION	N OF WATER	R WELL:	Fraction				Se	ction Number	Towns	ship Numbe	r	Range Number		
County:	Sedo	wick	NE	<sub>14</sub> N	NE ;	4 NV	V 1/4	35	Т	26	s	R 1	Ε	
Distance and	direction from	n nearest town	or city stre	et address					· ·		l	·· ·		
4111 E. 37	th St Wi	chita	or only on a										j	
		R: Koch In	dustrie	s. Inc.										
	Pay #	: 4111 E.	37 <sup>th</sup> St	o,o.					Board o	f Aprioudture	o Division	of Water Res		
RK#, St. Addi	ress, box #	Wichita	Kanea	c 6724	۵					-		or water Res	sources	
City, State, ZI	P Code	ATON WITH	, Nalisa	5 0/24	<del>5</del>				Applica	tion Number	<u>r:</u>			
	SECTION BO		4 DEPTH	OF COME	PLETED	WELL	į	ft. ELE	VATION:					
<b>→</b>	X							i <b>ry</b> ft						0
	1 1													
	NW	NE \						t. below land s						띪
0	į			Pump test	t data:	Well water	er was	f	t. after	h	ours pump	ing	gpm	USE
₩ W —	<del>:                                    </del>	<del>-  </del>	Est. Yield		gpm:	Well water	er was	1	t. after	h	ours pump	ing	gpm	m
	i	į   E	Bore Hole I	Diameter	8	in. to		<b>5</b> supply r supply	ft. and		in. to		ft.	ONLY
ļ	SW	SE	WELL WAT	TER TO BI	E USED	AS: 5 1	Public water	supply	8 Airc	onditioning	11 In	jection well		∹
1 1		i 1 l										ther (Specify	below)	ĺ
٧ L			2 Irrig	gation 4	Industr	ial 7 I	Lawn and ga	rden (domesti	c) 10 Mo	nitoring well	<u> </u>			
	S	1	Was a chei	mical/bact	eriologica	al sample	submitted to	Department?	Yes	No X	If yes, mo	/day/yr samp	le was	
		1	submitted		_					sinfected? Y				
5 TYPE OF	BI ANK CAS			5	Wrough	ht Iron	8 Cond	crete tile						1
			'P\		•			er (specify belo		001110.	Welded	····		
1 Stee		了 3 RMP(S	or)				nt 9 Othe	si (specify beit	ow)			Flu	- h	ĺ
2 PVC		4 ABS			Fibergl						Threaded			1
Blank casing	diameter	1	in. to	2.5	ft., Di	a	in	. to	ft., Dia		in.	to	ft.	
Casing heigh	t above land	surface	Flush	in.,	weight		0.703	lbs./ft.	Wall thickn	ess or gaug	ge No.	SCH.	40	
		ERFORATION			-		7	PVC	1	0 Asbestos	-cement			
1 Stee	4	3 Stainles	ss steel	5	Fiberal	lass	- 8	RMP (SR)	1	1 Other (sp	ecify)			١.
2 Bras		4 Galvani	ized steel	6	Concre	ete tile	g	ABS	1:	2 None use	ed (open h	ole)		1 -
		ION OPENING				5 Gau	zed wrapped	1	8 Saw o	cut	11	None (open	n hole)	
	tinuous slot		Mill slot				e wrapped		9 Drille				,	
	vered shutter	-		ed e			ch cut							
		INTERVALS:		2.5				ft.	Erom	(opoony)	ft to			
SCREEN-PE	KFOKATED	INTERVALS.												
								ft.						고
GRA	VEL PACK II	NTERVALS:	From	1.5				ft.				. <b></b>	ft.	
			From			ft. to		ft.	From		ft. to			-
6 GROUT N	MATERIAL:	1 Neat ce	ement	2 Ce	ment gro	out	3 B	entonite	4 Other					
Grout Interva	ls From	0.5 f	ft. to	1.5	ft. From	n	ft	. to	ft.	From		ft. to	ft.	
What is the n		e of possible co							stock pens			oned water w		
1 Sep		•	4 Lateral			7 Pit priv	/v		storage			I/ Gas well		
2 Sew			5 Cess p				ge lagoon		lizer storage			(specify below	w)	
	ertight sewer		6 Seepag			9 Feedy			cticide stora			,0,000, 20.0.	,	
Direction from	•	mics	о оссра	go pit		0 1000	u.u	How man		.90				-
FROM	TO	CODE	- · ·	ITHOLOG	IC LOG		FROM		1001:	PLUGG	ING INTE	RVALS		1
0.0	0.3		phalt											1
			, Lean C	Clav. wit	h sand.	gray to								6
0.3	3.5		k brown	,		, 3,								۱ ۲
3.5	5.0	CL Lea	an Clay,	dark bro	wn to b	rown								1
														1
														1
														1
														1
														7
														7
														1
														1
														1
7 CONTRA	CTOR'S OR	LANDOWNER	R'S CERTIF	FICATION	: This wa	ater well w	vas (1) const	ructed, (2) rec	onstructed	or (3) plugge	ed under m	ny jurisdiction	and was	7
<del>                                     </del>				08/27/0										
completed of								this record is		-	•			
ł .		icense No			531			s Water Well F		completed o	on (mo/da)	(yr) 09/	<b>24/09</b>	-
under the bu				chnical				by (signature		Lour		ehe_		_
		ease fill in blanks Topeka, Kansas											)00 S W	