under the business name of

GSI Job No. 097320 MW-28D WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number SE 1/4 SW 1/4 Sedgwick 34 26 1 Ε County: Distance and direction from nearest town or city street address of well if located within city? 3600 N. Hydraulic, Wichita 2 WATER WELL OWNER: The Coleman Company, Inc. RR#, St. Address, Box # : 3600 N. Hydraulic Board of Agriculture, Division of Water Resources Wichita, KS 67219 City, State, ZIP Code Application Number: LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION: AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 14.56 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr NE -- NW -Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8 in. to 40 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) W ŚE 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes _____ No X ___ If yes, mo/day/yr sample was Water Well Disinfected? Yes No X submitted 5 TYPE OF BLANK CASING USED: 5 Wrought Iron CASING JOINTS: Glued ____ Clamped 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 30 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface Flush in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) 1 Steel 3 Stainless steel 5 Fiberglass 6 Concrete tile 9 ABS 4 Galvanized steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 3 Mill slot 6 Wire wrapped 1 Continuous slot 9 Drilled holes 7 Torch cut 10 Other (specify) 2 Louvered shutter 4 Key punched From 30 ft. to 40 ft. From ft. to ft. SCREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to ft. **28** ft. to **40** ft. From ft. to ft. From GRAVEL PACK INTERVALS: ft. to From ft. From 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 0.5 ft. to 28 ft. From ft. to ft. From ft. to ft. From ft. to What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 4 Lateral lines Septic tank 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? CODE LITHOLOGIC LOG FROM PLUGGING INTERVALS FROM TO 20 0 Clay 26 20 Sand, fine to coarse grained 26 33 Sand, fine to coarse grained, some 33 40 pebbles 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 10/09/09 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 11/03/09

Geotechnical Services Inc.

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

by (signature) 💹

æ