4 I OCATIO	ON OF WATER	3 \A/E1 .	Fraction				Cont	on Numb	Tournahin M	T 1: N 1		NI b	
_			1				1					Number	_
	Sedg							34	↑ 26	<u> </u>	R	1	Ε
	d direction from		or city street	addres	ss of well if	flocated with	nin city?						
	lydraulic, V												
2 WATER	WELL OWNER	ર∶ The Co	leman Co	mpa	ny, Inc.								1
RR#. St. Ad	dress, Box #	: 3600 N.	Hydrauli	С					Board of Agric	culture. Divi	ision of Wate	er Resour	rces
City State	ZIP Code	Wichita	KS 672	19					Application N				
LOCATE	WELL'S LOC	ATON WITH											
3 AN "X" IN	N SECTION BO	OX:	4 DEPTH O	F COM	PLETED \	WELL	28.5	ft. EL	EVATION:				
T			Denth(s) Gro	indwat	er Encoun	tered 1	14 7	'8	ft. 2	f+	 ว		_ft.
	i I												··"
 	NW+	NE							d surface measured				
1	^	i	P	ump te	st data: \	Nell water w	as		ft. after	hours p	umping	g	
₹ W		- ii ∈ ı	Est. Yield		gpm: \	Well water w	as		ft. after	hours p	oumping	g	pm
7	1		Bore Hole Dia	ameter	8	in. to	28.	5	ft. after	ir	n to		ft.
	sw	se	WELL WATE	R TO E	BE USED A	AS: 5 Pub	lic water su	pply	8 Air condition	ning 1	1 Injection	well	
	1	i	1 Dome	estic	3 Feed lot	6 Oil f	ield water s	supply	9 Dewatering	1	2 Other (Sp	ecify belo	ow)
→ ∟	_ <u>i</u>	<u>i</u>	2 Irrinat	ion	4 Industria	al 7 law	n and nard	en (dome	ft. and 8 Air condition 9 Dewatering estic) 10 Monitorin	a well			.
	S		gu					on (201110	ene, it intermedial	-			
		1		cal/bac	teriologica	i sample sub	mitted to E		nt? Yes No 🕽				as
			submitted					\	Water Well Disinfect	ed? Yes		10 X	
5 TYPE O	F BLANK CAS	ING USED:		5	Wrough	t Iron	8 Concre	ete tile	CASING JOI	NTS: Glue	d C	Clamped	
1 Ste	eel	3 RMP (S	SR)			s-Cement				Weld			
2 PV		-	,						·			Fluck	
		4 ABS			7 Fibergla	ISS				Threa	aea	riusn	
Blank casing	g diameter	2	in. to	8.5	ft., Dia		in. t	0	ft., Dia		in. to		_ft.
Casing heig	ht above land	surface	Flush	in.,	weight	0.	703	lbs./	ft. Wall thickness or	gauge No.	SC	CH. 40	.
	CREEN OR P				•		7	PVC	10 Asb				
1 Ste		3 Stainles			Eiberola				11 Oth				
2 Bra			ized steel		Concret	o tilo	0	ABS	12 Nor	er (specify)			
	R PERFORAT			,					8 Saw cut			anan hal	_,
						5 Gauzed					11 None	open noi	a)
	ntinuous slot		Mill slot			6 Wire wr			9 Drilled holes				
2 Lou	uvered shutter	4 1							10 Other (spec	cify)			
SCREEN-P	ERFORATED	INTERVALS:	From	18	. 5 ft	t. to	28.5	ft	t. From	ft.	to		ft.
									t. From				
GR	AVEL PACK IN	JTFRVALS:	From	16	.5 ft	t to	28.5	ft	t. From	ft	to		4
0,0	AVEETAORII	TILITATEO.											- 1
-			From		π	. 10		<u></u>	t. From	π.	to		ft.
	MATERIAL:	1 Neat co	ement	2 C	ement grou	ut	3 Ben	tonite	4 Other	 -			
Grout Interv	als From	0.5 f	t. to 16	5.5	ft. From		ft. t	0	ft. From		ft. to		ft.
What is the	nearest source	e of possible co	ontamination:						estock pens		andoned wa		
1 Se	4 Lateral lin		7	Pit privy			iel storage		well/ Gas v				
	5 Cess poo						ertilizer storage	16 0	har /annaifu	halaw)			
			•				90011			10 01	ner (specify	Delow)	
	atertight sewer	iii les	6 Seepage	ρlt	9	Feedyard			secticide storage				
Direction fro		0005		101.00	NO 1 6 6		EDO:		any feet?				
FROM	TO	CODE		1ULO0	SIC LOG		FROM	то	PL	UGGING I	NTERVALS		
0	22	Cla											
22	27		nd, fine to	coarse	grained								
27	28.5	Cla	y										
								1					
													\neg
								1					-
	1							+					
	-							 					
7 60:	1070715 55		10 0555-F				(4)						
CONTR	ACTOR'S OR	LANDOWNER				er well was	(1) construc	ted, (2) re	econstructed, or (3) p	lugged und	er my jurisdi	ction and	was
completed of	on (mo/day/yr)		10	0/08/0	09		and th	is record	is true to the best of	ny knowle	dge and beli	ief. Kans	as
	Contractor's L				531				Recogniwas comple		-		
!			Geotech			es Inc		(signatur		011 (1110			
	USINESS NAME								ment of flealth and En	dironmant D	Uron: of Mr.	or 1000 0	101
Jackso	on St., Ste. 420.	Topeka, Kansas	s 66612-1367.	Teleph	one: 913-2	96-5545. Ser	nd one to W	ATER WEI	LL OWNER and retain	one for your	records	er, 1000 S	VV