MW-31

1 LOCATIO	ON OF WATER	R WELL:	Fraction				Section	on Number	Township Num	ber	Range Numb	er
County:	Sedg	wick	SE	½ S	W 1/4	NW	1/4	34	т 26	s	R 1	Е
Distance and	d direction fror	n nearest town			of well if	located with	hin city?					
	łydraulic, V											
		₹: The Co			y, Inc.							
RR#, St. Add	dress, Box #	3600 N.	Hydrau	lic					Board of Agricult	ture, Divis	sion of Water Reso	urces
City, State, 2	ZIP Code	Wichita	, KS 67	219					Application Num	ber:		
	WELL'S LOC		4 DEBTH	OF COME	DIETED W	/E11	28.5	4 FIE\	/ATION:			
	SECTION BO		JUEFIN	or Colvir	- Engage	red 1	14 9	11 4	7ATION.	4		
T I	i 1		Depth(s) Groundwater Encountered 1 14.91 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr									
 	NW	NE	Pump test data: Well water wasft. afterhours pumpinggpm								· }	
<u>•</u>	^ i			Pump test	data: W	ell water w	vas		t. after	hours p	umping	gpm c
₹ W -	1	 	Est. Yield		gpm: VV	ell water w	vas	<u>.</u> †	t. after	hours p	umping	gpm r
	1	;	Bore Hole D	Diameter	B FIGED A	in.to	28.	D nnlv	ft. and 8 Air conditioning	in.	. to	ft.
	SW	SE	1 Don	nestic 3	Feed lot	o. o rui. 6 Oil:	field water su	upply	8 Air conditionir 9 Dewatering	12	Other (Specify b	elow)
↓ L			2 Irria	ation 4	Industrial	7 lav	n and nard	en (domestir	c) 10 Monitoring w	vell	(,	,
<u> </u>	S								Yes No X			
				nical/pacte	enological	sample sui	omitted to D					was
F T T O	5 BL 44 II 4 O 4 O		submitted		147		0 0		ter Well Disinfected?		· · · · · · · · · · · · · · · · · · ·	
	F BLANK CAS				Wrought			te tile			dClamped	d
1 Ste		3 RMP (S	sK)				9 Other (specify belo		Weld		
2 PV		4 ABS			Fiberglas						led Flus	
Blank casing	g diameter	2	in. to	18.5	ft., Dia		in. to		ft., Dia		in. to	ft.
Casing heig	ht above land	surface	Flush	in., v	weight	0.	703	lbs./ft.	Wall thickness or ga	auge No.	SCH. 40)
TYPE OF S	CREEN OR P	ERFORATION	I MATERIAI	L:			7	PVC	10 Asbest	tos-ceme	nt	
1 Ste	eel	3 Stainles	ss steel	5	Fiberglas	ss	8	RMP (SR)	11 Other	(specify)		
2 Bra			ized steel	6	Concrete	tile						
		ION OPENING					d wrapped		8 Saw cut		11 None (open h	ole)
1 Co	ntinuous slot	-	Mill slot				rapped		9 Drilled holes			
	uvered shutter					7 Torch o			10 Other (specify	/)		
SCREEN-P	ERFORATED	INTERVALS:							From			
			From		ft.	to		ft. i	From	ft. t	0	ft. ;
GR.	AVEL PACK II	NTERVALS:	From	16.5) ft.	to	28.5	ft. I	From	ft. t	0	ft.
			From		ft.	to		ft. I	From	ft. t	0	ft.
	MATERIAL:							tonite				
Grout Interv	als From	0.5	ft. to 1	16.5	ft. From		ft. to	0	ft. From		ft. to	ft.
		e of possible c							stock pens		andoned water we	
1 Se	ptic tank		4 Lateral	lines	7	Pit privy		11 Fuel	storage	15 Oil	well/ Gas well	
	wer lines		5 Cess po			Sewage la	U	12 Fertil	izer storage	16 Oth	ner (specify below)	
3 Wa	atertight sewer	lines	6 Seepag	je pit	9	Feedyard		13 Insec	cticide storage			
Direction fro		0005		T. 101 - 5 :	010-			How many			-	
FROM	TO 21	CODE		THOLOGI	C LOG		FROM	ТО	PLUC	GING IN	NTERVALS	
21	21 27	Cla	nd, fine to		arainad			-				
27	28.5	Cla		COdise	granieu							
<u></u>	20.0	518	.1				 	 				
	 							1				
	ļ											
								1				
	-	ļ						1				
-100:	10705:0.0=	1 4415 611111	NO 0555	10 A T 10 1			777	1 (5)	<u> </u>			
						er well was			onstructed, or (3) plug			
completed	on (mo/day/yr)			10/08/0	9				true to the best of my			
Water Well	Contractor's L	icense No.		5	31				ecom was complete	d on (mo	(day/yr) 11/0	3/09
	usiness name		Geotec					(signature)				
									nt of Health and Environment of Health and retain on			sw