WATER W	ELL R	ECORD	Forn	n WWC-5	D	ivision of V	Vater Res	sources; Ap	p. No.		
1 LOCATIO	N OF W	ATER WELL:	Fraction			Section 1	Vumber	Townsh	nip Number	Range Number	
County:	gwick	NE 1/4	Clohal Da	2	T	26 s	R 1 E				
County: Sedgwick NE ½ NE ½ SW ½  Distance and direction from nearest town or city street address of well if located within city?  Township Promise Range Number 150 Miship Promise Range Numbe											
3255 N Arkansas, Wichita, 67204							Longitude: W 97 34499 °				
2 WATER WELL OWNER: Gas Station (KDHE T&M)						Elevation: RIM: 1317.97; TOC: 1317.54					
RR#, St. Address, Box # : 1000 SW Jackson, Ste 410						Datum: above mean sea level Data Collection Method: legal survey					
City, State, ZIP Code : Topeka, KS 66612-1367 Data Collection Method: legal survey											
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 20.5 ft.  LOCATON MW4											
WITH AN		Denth(s) Grou	ndwater En	countered 1					Α 2		
SECTION		WELL'S STA	TIC WATE	BIEVEI	12 86	ft below!	and surf	face mages	II. 3	ft. lay/yr <b>8/18/09</b>	
SECTION N	DOA.	Pum	n test data:	Well water	12.00	ii. below i	anu sun Fafter	iace illeast	hours numni	ing gpm	
	1 1	Est. Yield	gnm.	Well water	was	f	t after		hours numni	ing gpin	
Est. Yield gpm: Well water was ft. after hours pumping graph WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well											
W   X   Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below 2 Irrigation 4 Industrial 7 Domestic (lawn & garden)   10 Monitoring well										er (Specify below)	
										- SW - SE -	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs											
S		Sample was su	hmittad				Water V	Vall Digin	footod? Voc	NI. X	
5 TYPE OF C	CASING	USED: 5	Wrought I	ron 8	Conc	rete tile	CAS	SING JOIN	VTS: Glued	Clamped	
1 Steel	3	RMP (SR) 6	Asbestos-(	Cement 9	Other	(specify b	elow)		Welde	d	
(2) PVC	4	ABS 7	Fiberglass			(-1)	020 11)		Thread	led X	
Blank casing di	ameter	2 in. to	10.5	t., Dia		in. to	ft	Dia	in.	to ft.	
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  2 PVC 4 ABS 7 Fiberglass Threaded X  Blank casing diameter 2 in. to 10.5 ft., Dia in. to ft., Dia in. to ft.  Casing height below land surface 0.43 ft., Weight Ibs./ft. Wall thickness or gauge No.  TYPE OF SCREEN OR PERFORATION MATERIAL:											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)											
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot (3) Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)											
1 Continuous slot (3) Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  SCREEN-PERFORATED INTERVALS: From 10.5 ft. to 20.5 ft. From ft. to ft.											
SCREEN-PERI	FORATE	D INTERVALS	: From	10.5	ft. to	20.5	ft. F	rom	ft. to	o ft.	
From ft. to ft. From ft. to									) ft.		
GRAVEL PACK INTERVALS:         From         8.5         ft. to         20.5         ft. From         ft. to           From         ft. to         ft. From         ft. to								oft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Sentonite 4 Other Concrete: 0-2 Grout Intervals From 2 ft. to 8.5 ft. From ft. to ft. From ft. to ft.											
Grout Intervals	Fron	1 2 ft. to	8.5 ft	. From	f	t. to	ft	. From		ft. to ft.	
What is the nearest source of possible contamination:											
1 Septic tan		4 Lateral li						secticide S		16 Other (specify	
2 Sewer line		5 Cess poo		ige lagoon (1				oandoned v		below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard  Direction from well? northeast  12 Fertilizer storage 15 Oil well/ gas well  How many feet? ~150ft											
							13011				
	0		LOGIC LO	G	FROM	M TO		PLUG	GING INTE	RVALS	
		rass, topsoil indy clay, brown	fine to me	adium			-				
0.5		ained, slightly n					-				
		asticity									
1.0 8.		nd, tan, fine gra	ined, nearl	y dry, low							
		asticity									
8.5		nd, tan, fine gra	ined, imma	iture mica,							
11 1		ghtly moist nd, tan, mediun	grained i	mmature			Flush	mount wa	iver from B	OW	
		ca, slightly mois		atui C			I lusii	mount wa	HOM D	<u></u>	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged											
under my jurisdiction and was completed on (mo/day/year)  Kansas Water Well Contractor's License No. 757  This Water Well Record was completed on (mo/day/year) 10/7/09											
		ctor's License No.					1 1 1		ay/year)1	<u>)/7/09</u>	
		Larsen & Ass			-	ature)					
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section. 1000 SW Jackson St., Suite 420. Fopeka, Kansas 6612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for											
Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.											