WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.

1 LOCATIO	N OF WATER	R WELL:	Fraction				Section	on Number	Towns	hip Number	Range	Number	
		wick	1		W 1/4	NW	1/4	34	Т	26 s	R	1 [E
Distance and		nearest town											
2 WATER V	VELL OWNER	: The Col	eman C	ompan	y, Inc.								\neg
RR# St. Add	Iress Box#	3600 N.	Hvdrau	lic	•				Board o	f Agriculture, Div	ision of Wate	er Resourc	es
City State Z	IP Code	Wichita	KS 67	219						ion Number:			
LOCATE	WELL'S LOCA	ATON WITH											
AN "X" IN	SECTION BO)X:	TOES IN	OF COMP	PLETED V	VELL	25	ft. ELEV	/ATION:				· ,
†										ft.			ft.
	N'W	NE V								sured on mo/day			
	xi	i		Pump test	data: V	Vell water v	vas	f	t. after	hours	oumping	gp	om c
₩ W	<u>^ </u>	EE	st. Yield		gpm: V	Vell water v	vas	f	t. after	hours	pumping		m i
7		E	Bore Hole I	Diameter	8.25	in. to	25		ft. and	<u>i</u> j	n. to		ft.
	-sw	SE V	WELL WAT	TER TO BE	E USED A	S: 5 Pul	olic water su	pply	8 Air c	onditioning 1	1 Injection		_
	į l									atering 1			w)
Y	S									nitoring well			
	Ŭ	\	Nas a chei	mical/bacte	eriological	sample su	bmitted to D			No X If yes			ıs
			submitted					Wa	ter Well Dis	infected? Yes		lo X	_
5 TYPE OF	BLANK CAS	ING USED:		5	Wrought	Iron	8 Concre	te tile	CASIN	G JOINTS: Glue	edC	lamped _	
1 Stee	el	3 RMP (S	R)	6	Asbesto	s-Cement	9 Other (specify belo	w)	Wel	ded		
2 PVC		4 ABS		7	Fibergla	ss				Threa	ded	Flush	
Blank casing	diameter	_ 2	in. to	20	ft., Dia		in. to		ft., Dia				ft.
Casing heigh	ht above land	surface	Flush	in., v	weight	0	.703	lbs./ft.	Wall thickn	ess or gauge No	SC	H. 40	
TYPE OF SO	CREEN OR PI	ERFORATION	MATERIA	٠L:			7	PVC	10	0 Asbestos-cem	ent		
1 Stee	el	3 Stainles	s steel	5	Fibergla	SS	8	RMP (SR)	1	1 Other (specify)		
2 Bras	SS	4 Galvani	zed steel	6	Concrete	e tile	9	ABS	12	None used (or	en hole)		
SCREEN OF	R PERFORAT	ION OPENING	S ARE:			5 Gauze	d wrapped		8 Saw o	cut	11 None	(open hole	:)
1 Con	ntinuous slot	3 N	/ill slot			6 Wire w	rapped						
2 Lou	vered shutter	4 K	• •			7 Torch			10 Other	(specify)			
SCREEN-PE	ERFORATED	INTERVALS:	From	20	ft	. to	25	ft. 1	From	ft.	to		ft.
			From		ftft	. to		ft. I	From	ft.	to		ft.
GR/	AVEL PACK I	NTERVALS:	From	18	ft	. to	25	ft. I	From	ft.	to		ft.
			From							ft.	to		ft.
6 GROUT	MATERIAL:	1 Neat ce	ement	2 Ce	ment grou	ıt	3 Ben	tonite	4 Other				
										From			
What is the	nearest source	e of possible co	ontamination	on:					stock pens				
1	otic tank		4 Lateral		7	Pit privy		11 Fuel	storage	15 O	il well/ Gas v	well	
2 Sev	5 Cess p	ool	8	Sewage I	agoon	12 Ferti	lizer storage	16 0	ther (specify	below)			
3 Watertight sewer lines 6 3				ge pit	9	Feedyard	ļ.	13 Insec	cticide stora	ge			
Direction fro	m well?							How many	y feet?				
FROM	ТО	CODE		ITHOLOG	IC LOG		FROM	ТО		PLUGGING	INTERVALS		
0	20		y, brown					ļ					_
20	25	1 1		o coarse	grained,	brown,							
20	25	With	gravei					+					
								 					\dashv
]
							-						
							ļ		 				
							-						
7 00177	10705'0 65	LANDONANIES	VC OFFI	CICATION	. This		(1)	-to-d (0) ====	amata d	a. (2) al d	dan mari kanda d		
-						ter well was				or (3) plugged un			
)								pest of my knowle			
1		icense No.			531	<u>.</u>				completed on m	o/day/yr) _	05/05/	10
under the b	usiness name	of		chnical			by	(signature)	1/2/	La /4	D	1000	104
Jackso	on St., Ste. 420,	ease tiil in blanks Topeka, Kansas	s and circle s 66612-13	tne correct	answers. 3 one: 913-2	sena inree o 296-5545. S	end one to W	ATER WELL	OWNER and	and Environment, d retain one for you	bureau of Wa ur records.	ner, 1000 S	vv