	WATER WELL RECORD FO	orm WWC-5 KS	A 82a-1212	
1 LOCATION OF WATER WELL:	FRACTION	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick	NE 1/4 SW 1/4 SW	1/4 30	T 26 S	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city? 3917 N. Athenian Ave. Wichita, Kansas				
2 WATER WELL OWNER: HOOP, Janice				
	7 N. Athenian Ave.		Board of Agri	culture, Division of Water Resource
	hita, Kansas	ZIP CODE:	Application Num	nber:
	DEPTH OF COMPLETED WELL: 52	ft.	ELEVATION:	
WITH AN "X" IN SECTION BOX:	epth of groundwater Encountered:	ft.	ft.	ft.
	ELL'S STATIC WATER LEVEL 15	FT. BELOW LAND SUF	RFACE MEASURED ON mo/o	day/yr: 9/1/10
NW NE	Pump test data: Well water	er was	ft. after hours	of pumping @ gpm
W W E E	Est. Yield: gpm Well water		ft. after hours	of pumping @ gpm
	Bore Hole Diameter 12 in.	to 52 ft.	and in.	to ft.
	/ELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public wate	er supply 7. Lawn ar	9. Dewateri	•
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well				
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample				
<u></u>	ubmitted	Was W	ater Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 1. Steel 3. RPM (SR) Welded Clamped				
1. Steel 3. RPM (SR) Welded Clamped 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26				
Blank casing diameter 5	in. to 32 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface:		2.35 lbs. / ft.	Wall thickness or gaug	
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)				
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1. Continuous slot 3. Mill s	slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key p	ounched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL	From 32 ft. to	52 ft.,	From ft.	to ft.
	From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS:	From 24 ft. to	52 ft.,	From ft.	to ft.
	From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat		3. Bentonite		onite hole plug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible c	contamination:	D. Livestock pens	·	
1. Septic tank 4. Lateral lines				16. Other (specify below)
2. Sewer lines 5. Cess Pool 5. Cess Pool 5. Cess Pool 6.				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? West How many feet? 10 ft. plus				
Direction from well? West From To	LITHOLOGIC LOG	From To	The state of the s	OGIC LOG
0 3 topsoil	ETTIOEOGIO EGO	170111	LITTOLO	OGIC EGG
3 15 clay				
15 27 fine sand				
27 52 medium sand	d.	F		

	To the second se			
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and				
was completed on (mo/day/year) 9/1/2010 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/3/2010				
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb				