	WATER WELL F	RECORD F	orm WW	C-5 K	SA 82a-121	2			
1 LOCATION OF WATER WELL:	FRACTION	ALL NIE	1	ON NUMBER			RANGE NUI		
Sedgwick Distance and direction from nearest town or ci	NW 1/4 NE	1/4 NE	1/4	31	Т 26	S	R 1E	E/W	
1/8 mile West of Seneca, South of 37th St. N. Wichita, Kansas (8 plugs on 1 permit)									
	CHITA, CITY OF					Board of Agric	culture, Division of Wa	ater Resource	
	5 N. Main chita, Kansas		715	CODE:		Application Num	20100		
3 LOCATE WELL'S LOCATION 4		WELL 4		CODE.	ELEVATION:	Application Non	ibei.		
WITH AN "X" IN SECTION BOX:	Depth of groundwater Encour		ft.			ft.		ft.	
	WELL'S STATIC WATER LE		FT. BELOV	W LAND SU	JRFACE MEASU	RED ON mo/d	ay/yr: 12/3/	10	
	Pump test	data: Well wa	ter was		ft. after		of pumping @	gpm	
w E	Est. Yield: gpr Bore Hole Diameter	m Well wa in.	ter was to	ft.	ft. after and	hours in.	of pumping @ to	gpm ft.	
	WELL WATER TO BE USE		10	н.	and (9. Dewaterii	44 Julius		
SW SE	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)								
	 Irrigation 4. Industri Was a chemical/bacteriological 		vater supply	8. Air con YES	nditioning	10. Monitorin	i g well vh <u>at</u> mo/day/yr wa	as sample	
S	submitted	sample submitted to	ораганска:		Vater Well Disinfe	ected?	YES N	0	
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 1. Steel 3. RPM (SR) World Clarged									
1. Steel 3. RPM (6. Asbestos-Ceme	nt 8. Concrete t	ile				Welded	Clamped	
Blank casing diameter 8	in. to	ft., Dia.	in.	to	ft., [Dia.	in. to	ft.	
Casing height above land surface:	36 in.,	Weight:	lb	s. / ft.	Wall this	ckness or gaug	ge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill		wrapped	7. Tor	ch cut	9. Drille	ed holes	11. None (op	pen hole)	
2. Louvered shutter 4. Key	punched 6. Wire wr	rapped	8. Sa v	w cut	10. Othe	r (specify) N	/A		
SCREEN - PERFORATION INTERVA	•	ft. to)	ft.,	From	ft.	to	ft.	
	From	ft. to)	ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS	From	ft. t	0	ft.,	From	ft.	to	ft.	
	From	ft. t	0	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug							g		
Grout Intervals: From 3 ft. to 23 ft., From ft. to ft., From						ft. to	ft.		
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy			10. Livestoc	k pens	13. Insecticide storage 15. Oil well/Gas well				
1 .				rage	14. Abandon water well		16. Other (specify below)		
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None apparent							parent		
Direction from well?	LITHOLOGIC LO		From	То	How ma		GIC LOG		
From To	LITHOLOGIC LOC	3	0	3	compacted t		JGIC LOG		
			3	23	bentonite ho	de plug			
			23	40	chlorinated	gravel			
				ļ <u>.</u>					
				ļ					
7 Contractor's or Landowner's Cer	rtification: This water well	se 1 constructs	d 2 ro	constructo	d or 3.	plugged	under my jurisdicti	on and	
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 12/3/2010 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/6/2010									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									
under the business name of Har	P Wen and I ump Se	1 1100	3, (3)	/	1 (лииз	. TUMP		