	WELL KEU		FUIII W	WC-3	וע	vision of wate	r Resources App. N	0		
1 LOCATION OF WATER WELL: County: SEDGWICK			Fraction ¹ / ₄ SE ¹ / ₄ SE	1/4 SW 1/4		on Number 27	Township No. T 26 S	Range Number R 1		
Street/Rural Address of Well Location; if unknown, distance & direction					Clobs	Clobal Positioning System (CPS) information:				
		ntersection: If at o	Latitu	Latitude: .37.:753899 (in decimal degrees) Longitude: .97: 310009 (in decimal degrees)						
2100 E. 37TH ST. NORTH, WICHITA, KS 67219						Elevation: (in decimal degrees)				
						Datum: WGS 84, NAD 83, NAD 27				
2 WATER WELL OWNER: CHEVRON EMC (BR1Y-RM. 3424) RR#, Street Address, Box #: 6111 BOLLINGER CANYON RD.						Collection Method: GPS unit (Make/Model:)				
RR#, Street Address, Box #: 6111 BOLLINGER CANYON RD. City, State, ZIP Code : SAN RAMON. CA 94583					☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey					
6744 1 B 4810 14, 671 0 4000						Est. Accuracy:				
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL										
	SECTION BOX: Depth(s) Groundwater Encountered (1)						ft. (2) ft. (3) ft.			
N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr										
Pump test data: Well water wasft. after							hours pum	ping gpm		
NW	NE E	EST. YIELDgpm. Well water wasft. afterhours pumpinggpm Bore Hole Diameter								
"		WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW SE Domestic Feedlot Oil field water supply Dewatering Oth										
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well → CP. ₹ - 4								CF. ~		
S If yes, mo/day/yr sample was submitted										
1 mile Water well disinfected? ☐ Yes ☑ No										
5 TYPE OF CASING USED: Steel PVC Other										
CASING JOINTS: Glued Clamped Welded Threaded										
Casing diameter										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)										
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous slot										
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) FILLER SAND PRE-TACKED SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft., From ft., ft.										
SCREEN-PERFORATED INTERVALS: From										
GRAVEL PACK INTERVALS: From										
From										
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other										
What is the nearest source of possible contamination:										
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)										
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well SECONDARY										
Direction from well										
	го	LITHOLOG	IC LOG	FROM	TO	LITHO. LO	OG (cont.) or PLU	GGING INTERVALS		
0 1	1' TOPS		4 4 4 4							
7.5' 2	8' SELT	CLAYEY	<u>CLAY</u> SILT	+,3'	-2′	4"x4"	VS' SOEKI	ABOVE GROWD		
	9' SHAL	7	اعلاق		9	+		COMPLETION		
ļ										
						CPF)	I JOB #10	a 63·8)		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗸 constructed, 🗆 reconstructed, or 🗔 plugged										
under my jurisdiction and was completed on (mo/day/year)										
under the business name of ROBERTS ENV. DRILLING. INC. by (signature)										
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies										
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at										
http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212 Check: W White Copy, Blue Copy, Pink Copy										