WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: SEDGWICK	Fraction  1/4 SE 1/4 SE 1/4 SW 1/4	Section Number Township No. Range Number T 26 S R 1  E W
Street/Rural Address of Well Location: if unknown distance & direction   Global Positioning System (GPS) information:		
from nearest town or intersection: If at owner's address, check here \(\sigma\). Latitude:37.753.368 (in decimal degrees)		
2100 E. 37TH ST. NORTH, WICHITA, KS 67219		Longitude: -97.309263° (in decimal degrees)
, , , , , , , , , , , , , , , , , , , ,		Elevation:
2 WATER WELL OWNER: CHEVE	0115110 (554) 514 6464)	<u>Datum</u> : <b>☑</b> WGS 84, □ NAD 83, □ NAD 27
011211	RON EMC (BR1Y-RM. 3424)	Collection Method:
C'ty Ctate ZID Calle	OLLINGER CANYON RD.	☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
SAN RA	AMON, CA 94583	Est. Accuracy: $\square < 3 \text{ m}, \square 3-5 \text{ m}, \square 5-15 \text{ m}, \square > 15 \text{ m}$
3 LOCATE WELL		
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL		
SECTION BOX: Depth(s) Ground	dwater Encountered (1)	ft. (2) ft. (3) ft.
		below land surface measured on mo/day/yr
Pump test data: Well water wasft. after hours pumping gpm		
EST. YIELDgpm. Well water wasft. after hours pumping		
W Bore Hole Diameter		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
SW SE Domestic		
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well → ? ! Д		
was a chemical		
	day/yr sample was submitted	
Water were districted: 1 Tes 12 No		
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded		
Casing diameter		
Casing height above land surface		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)		
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)		
SCREEN-PERFORATED INTERVALS: From		
From		
GRAVEL PACK INTERVALS: From 32 ft. to		
From		
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout  ☐ Bentonite ☐ Other		
		ft. to ft., From ft. toft.
What is the nearest source of possible conta		<b>—</b>
Septic tank Lateral lin	nes	
☐ Watertight sewer lines ☐ Seepage p		
Direction from well (ON: SITE).		from well ON-SITE SOURCE
FROM TO LITHOLOG		TO LITHO. LOG (cont.) or PLUGGING INTERVALS
O 1.5' SANDY SILT	-	The state of the s
1.5' 6' STLTY CLAY		
6' 13.5' CLAYEY SILT	+3'	2' 4"x4"x5' STEEL ABOVE GROWN
13.5' 16' SILTY CLAY		WELL PROTECTION COMPLETEON
16' 26' SANDY STLT		777
26' 32.5' SELT WITH TH	RACE CLAY	
AND SHALE F		
32.5' 33' SHALE		
		(REDI JOB# 109098)
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, or plugged		
under my jurisdiction and was completed on (mo/day/year) . 1.2/12/10. and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 788 This Water Well Record was completed on (mo/day/year) 1/2.4//		
under the business name of ROBERTS ENV. DRILLING. INC. by (signature)		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies		
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdheks.gov/waterwell/index.html.		
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy		