WATE	CR WE	LL RECORD	Form WWC	-5	Division of Wate	r Resources App. N	0	
		n of water well: gurk	Fraction 14 SW 14 SW 14 M		ection Number	Township No. T 26 S	Range Number R [ [ ]E [ ]W	
Stre	et/Rural	Address of Well Location;		Clobal Positioning System (CPS) information:				
		town or intersection: If at		. L	Latitude:37. 8193 (in decimal degrees)			
		1. meridian, Valle		_ L	Longitude: .7.1:			
Elevation: ./, 2.7.7								
2 WATER WELL OWNER: BP North American Products Attaching Richfeld Collection Method:								
RR#, Street Address, Box #: 501 Wertlake Park Blw. Company GPS unit (Make/Model: Carnic								
Cit	City, State, ZIP Code : Houston, TX 77079					☐ GPS unit (Make/Model: Commit C5		
Cit.	y, State,	En code . Prouston,	אדסדר או	Es	st. Accuracy:	3 m. 143-5 m.	5-15 m. $\square > 15$ m	
Est. Accuracy:								
1	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL							
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1)							
	WELL'S STATIC WATER LEVEL/5. 89ft. below land surface measured on mo/day/yr. 4.21-11							
Pump test data: Well water wasft. afterhours pumping							oinggpm	
EST. YIELDgpm. Well water wasft. afterhours pumping						ping gpm		
W ELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
		□ Domostic	TO BE USED AS:   Put	olic water su	ipply	otnermai 🔲 II	njection well	
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
	s					ies 🖭 No		
	S If yes, mo/day/yr sample was submitted							
		ASING USED: Steel				••••		
CASIN	IG JOIN	TS: Glued Clam	iped   Welded   I	hreaded	- 0 D:			
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface. Flysh in., Weight								
Steel Stainless Steel PVC Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Control of the Control								
Grout Intervals: From								
What is the nearest source of possible contamination:  ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)								
Sewer lines								
□ Watertight sewer lines □ Seepage pit □ Feedyard □ Fertilizer storage □ Oil well/gas well Fvel Teminal								
	tion fro	n well		stance from	well	•••••		
FROM	ТО	LITHOLOGI	C LOG FRO	OT MC	LITHO, LO	G (cont.) <u>or</u> PLUC	GGING INTERVALS	
0	10	. Clay, firm						
10	13	Silty clay, firm						
13	25	Sand-median gonin	al Clay Stringer					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No								
under the business name of Below Ground Lyr face. The by (signature) with the business name of Below Ground Lyr face. The by (signature) with the business name of Below Ground Lyr face. The business name of Below Ground Lyr face.								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
SA 82a-1212 Check: (White Copy, Blue Copy, Pink Copy								