		WATER W	ELL REC	ORD F	orm WV	VC-5 K	SA 82a-1	212			
1 LOCATION OF WATER W	VELL:	FRACTION			1	TION NUMBE	R TOWNS	HIP NUMBER	RANGE N		
Sedgwick		NW 1/4	NW 1/		1/4	29	T	26 S	R 1I	E/W	
Distance and direction from ne	earest town or city st	reet address of wel	Il if located within	city?		ā					
OT WATER WELL OW	NED CONC	OCO-PHILI	IDC		.	4 cons	struct on 1	permit			
2 WATER WELL OWI		E. 37th N.	TILO					Board of Agr	riculture, Division of V	Vater Resource	
CITY, STATE: Wichita, Kansas						IP CODE: 6	7219	Application Nu	olication Number: 20110303		
3 LOCATE WELL'S LOCA	1.1	EPTH OF COMP	I ETED WELL	: 35		IF CODE.	ELEVATION		moer.		
WITH AN "X" IN SECTIO	ON BOX:	h of groundwater			ft			ft.		ft.	
N		L'S STATIC WA		8			IDEACE MEA	SURED ON mo/	day/yr: 7/13		
	NE		mp test data:	Well wat		W LAND S	ft, after		s of pumping @	y I I gpm	
1 1 ' 1		Est. Yield:	gpm	Well wat			ft. after		s of pumping @	gpm	
w Wije	E Bor	e Hole Diameter		in.	to 3	35 ft		in.	to	ft.	
-		L WATER TO B	BE USED AS:					9. Dewateri	ing 11. Inje	ction well	
sws	1			5. Public wa	ter supply		and garden o	-		pecify below	
		-		6. Oil field w		*	nditioning	10. Monitori	ng well what mo/day/yr v	vas samnie	
s		s a chemical/bacte nitted	nological sample	submitted to L	epartment?	YES Was \	NO Water Well Dis	•		NO	
5 TYPE OF CASING	G USED:	F 14/		7 [:	9.0	ther (Specifi	(below) C	ASING JOINTS:	Glued	Threaded	
1. Steel	3. RPM (SR)	5. Wrought		7. Fiberglass	SC	но (ороси) H-40	, 50.011,		Welded	Clamped	
2. PVC	4. ABS	6. Asbestos	s-Cement 8	3. Concrete ti	le SC	11-40				•	
Blank casing diameter	8 in	ı. to	20 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height above lar	nd surface:	12 in.,		Weight:	5.52 I	bs. / ft.	Wall	thickness or gau	ge No332		
TYPE OF SCREEN OR				====							
1	tainless Steel	5. Fiberglass	_	PVC	9. A			Other (specify)			
2. Brass 4. G	ialvanized	6. Concrete T	Tile 8.	. RMP (SR)	10. A	sbestos-Ce	ment 12.	None used (open	hole)		
SCREEN OR PERFORA											
1. Continuous slot	3. Mill slot	5. 0	Gauzed wrap _l	ped	7. To	rch cut	9. D	rilled holes	11. None (d	open hole)	
2. Louvered shutter	4. Key pur	iched 6. \	Wire wrapped	I	(8. Sa	w cut	10. O	ther (specify)			
SCREEN - PERFORATIO	ON INTERVAL	From	20 ft.	to	35	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
GRAVEL PACK	INTERVALS:	From	20 ft.	to	35	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft,	to	ft.	
6 GROUT MATERIALS	S: 1 Neat ce	ment	2 Cement	Grout		3. Bentonite			tonite hole pl		
Grout Intervals: 1. Neat cement 2. Cement Grout Grout Intervals: From 0 ft. to 20 ft., From					ft.			From	ft. to	∽ 5 ft.	
What is the nearest source of possible contamination:							ft.,				
1. Septic tank	4. Lateral li	iiica	. Pit privy					cticide storage	10 Other (a-	15. Oil well/Gas well	
2. Jewei intes								ndon water well	, ,	3. Other (specify below) None Apparent	
3. Watertight sewer lin	ne 6. Seepage	pit 9	. Feed yard	1	2. Fertilize	r storage			None Ap	эраг спі	
Direction from well?		ITUOL OCIO	2100		T	T -	How	many feet?	2010 1 00		
From To 0 3 to		ITHOLOGIC	LUG		From	To		LITHOLO	OGIC LOG		
	psoil ne sand					· · · · · · · · · · · · · · · · · · ·					
	edium sand									-	
	-					1		.			
					<u></u>	<u> </u>					
											
		· - · · · · · · · · · · · · · · · · · · 									
						1				· · · · · ·	
					†						
7 Contractor's or Land	downer's Certifica	tion: This water	well was 1	constructed) 2 re	constructed	d or 3,	plugged	under my jurisdic	tion and	
was completed on (mo		7/13/2011					knowledge an		, ,2210		
						•	_		1/2011		
Kansas Water Well Co							l on (mo/day/y 		5/2011		
under the business nar	me of Harn W	Jall and Dun	nn Sarvica		by (si	anature)	-	てふみみ、の	· 7/~		

Harp Well and Pump Service by (signature) Todd S. Havp