WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: TOWNSHIP NUMBER RANGE NUMBER SECTION NUMBER \mathbf{SW} 26 Sedgwick NW 1/4 NW1/4 S 1E E/W Distance and direction from nearest town or city street address of well if located within city? 6749 N. Meridian Wichita, Kansas WATER WELL OWNER: PROSSER, Margaret Board of Agriculture, Division of Water Resource 5 Creekwood Circle RR#,ST. ADDRESS,BOX #: ZIP CODE: 75080-2672 CITY, STATE: Richardson, TX, Application Number: 50 4 DEPTH OF COMPLETED WELL: **ELEVATION** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was hours of pumping @ ft. after gpm NE-Est. Yield: Well water was ft. after hours of pumping @ gpm Φ ⋛ Bore Hole Diameter 12 to 50 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample (NO) Was a chemical/bacteriological sample submitted to Department? (YES) NO submitted Was Water Well Disinfected? 5 TYPE OF CASING USED: Threaded 9. Other (Specify below) CASING JOINTS: Glued 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 5 30 ft. ft.. Dia. ft... Dia Blank casing diameter to in in in. ťΩ to 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3 Mill slot 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched 50 SCREEN - PERFORATION INTERVAL 30 ft. ft.. From to From ft. From ft. to ft. From fŧ to ft. 24 ft. 50 GRAVEL PACK INTERVALS: ft., ft. From From to ft. ft. From to ft.. From ft Other **GROUT MATERIALS** 6 2. Cement Grout bentonite hole plug 3. Bentonite 1. Neat cement Grout Intervals: 4 24 ft. From ft., From ft. to From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool None Apparent 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? Direction from well? From To LITHOLOGIC LOG From Τo LITHOLOGIC LOG 0 topsoil 10 3 clay 10 18 fine sand 18 30 clay 30 50 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3. plugged under my jurisdiction and

was completed on (mo/day/year) 12/9/2011 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/12/2011

under the business name of Harp Well and Pump Service by (signature) Todd S. Horb