WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. Township Number Range Number Section Number 1 LOCATION OF WATER WELL: Fraction Sedgwick SW 1/4 SW 1/4 SW 1/4 27 **26** s 1 R County: Distance and direction from nearest town or city street address of well if located within city? 3850 N. Hydraulic - Wichita 2 WATER WELL OWNER: USD 259 School Service Center RR#, St. Address, Box # : 3850 N. Hydraulic Board of Agriculture, Division of Water Resources City, State, ZIP Code : Wichita, KS 67219 Application Number: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 19.51 ft. below TOC measured on mo/day/yr 05/22/12 -- NW ----- NE ---Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8 in. to 33 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) W - sw ---- SE -2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes No X submitted 5 Wrought Iron CASING JOINTS: Glued Clamped 5 TYPE OF BLANK CASING USED: 8 Concrete tile Welded 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Threaded Flush 4 ABS 2 PVC 7 Fiberglass Blank casing diameter 2 in. to 21 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 1 Continuous slot
2 Louvered shutter 9 Drilled Holes

10 Other (specify)

ft. 4 Key punched 7 Torch cut 2 Louvered shutter SCREEN-PERFORATED INTERVALS: From 21 ft. to 33 ft. From ft. to ft.
 From
 ft. to
 ft. From
 ft. to
 ft. From

 19.3
 ft. to
 33
 ft. From
 ft. to
 ft. ft.
 GRAVEL PACK INTERVALS: ft. From ft. to ft. to From 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 1.5 ft. to 19.3 ft. From ft. to ft. From ft. to ft. 14 Abandoned water well What is the nearest source of possible contamination: 10 Livestock pens 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 13 Insecticide storage 6 Seepage pit 9 Feedvard How many feet? Direction from well? LITHOLOGIC LOG TO CODE FROM PLUGGING INTERVALS TO FROM 0 2 Topsoil 贸 Silty Clay, fine sand lenses between 23.4 15' and 17', little coarse sand below 21' 23.4 24 Sand, fine grained 24 Sand, fine to coarse grained **GPS: UTM** Northing: 4179852 Easting: 648252 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr)

05/22/12

and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No.

531

This Water Well Record was completed on (mo/day/yr)

07/13/12 r the business name of Geotechnical Services Inc. by (signature)

INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.