WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NWSedgwick \mathbf{SW} 1/4 NW1/4 1/4 18 Т 26 S 1E E/W R Distance and direction from nearest town or city street address of well if located within city? 2320 W. 60th No. Wichita, Kansas **BIGGS**, Nicholas WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2320 W. 60th No. Wichita, Kansas CITY, STATE: ZIP CODE Application Number: LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 45 ft. ELEVATION: WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 12/19/12 Well water was Pump test data: -NW ΝE ft. after gpm Est. Yield: gpm Well water was ft. after hours of pumping @ <u>o</u> apm Ξ Bore Hole Diameter 12 to 45 and in. ft. WELL WATER TO BE USED AS 11. Injection well Dewatering SW SE-7. Lawn and garden only 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter 25 Dia. in. to ft.. in to ft Dia ft. 12 2.35 Casing height above land surface: Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 7. PVC 9. ABS 11. Other (specify) 5. Fiberglass 1. Steel 10. Asbestos-Cement 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 10. Other (specify) 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 25 ft. 45 ft., From to From to ft. From ft. to ft.. From ft. to GRAVEL PACK INTERVALS: 24 to 45 From ft.. From ft ft. From ft. to ft., From to ft. **GROUT MATERIALS** Other bentonite hole plug 1. Neat cement 2 Cement Grout 3. Bentonite Grout Intervals: 4 ft From 24 ft., ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 2. Sewer lines 5. Cess Pool 14. Abandon water well 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line Northwest Direction from well? How many feet? 50 ft. plus LITHOLOGIC LOG From Τо From To LITHOLOGIC LOG 0 topsoil 3 10 clav 10 25 fine sand 25 medium sand 45 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and was completed on (mo/day/year) 12/19/12 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12-21-2012 Todd S. Harp under the business name of Harp Well and Pump Service by (signature)