			ELL RECORD	FOI	rm WW		SA 82a-12			
1 LOCATION OF WATER Sedgwick	well: <b>NF</b> .	FRACTION SE 1/4	NE 1/4	SE 1	SECT	TON NUMBER	TOWNSHII	P NUMBER  6 S	RANGEN R 11	
Distance and direction from				SE	1/4	72 11		0 3	17 14	<u> </u>
101 W. Chippewa Kechi, Kansas										
2 WATER WELL OV		ON, James						Board of April	culture, Division of V	Nater Resource
RR#,ST. ADDRESS,B		. Chippewa						-		Valer Nesource
CITY, S		, Kansas		85		CODE:	EL EVATION:	Application Num	ber:	
3 LOCATE WELL'S LOC WITH AN "X" IN SECT	ION BOX:	EPTH OF COMP		03	ft.		ELEVATION:	4		4
N N		h of groundwater	_	0 F	ft.	ALL AND OU	DEAGE MEAC	ft.		ft. <b>5/13</b>
	<u> </u>	L'S STATIC WA	-	ell water		W LAND SU	ft, after	JRED ON mo/d hours	of pumping @	gpm
Φ NW	- NE   	Est. Yield:	•	ell water			ft. after		of pumping @	gpm
M   M   M   M   M   M   M   M   M   M	E Bor	re Hole Diameter			to <b>8</b>	<b>5</b> ft.	and	in.	to	ft.
sw		L WATER TO B				7 1 awn a	nd garden only	9. Dewaterir	·9	ction well
	1 "				supply er supply			10. Monitorin		pecify below)
	1	=	nological sample submit			YES	NO	; If yes, w	vhat mo/day/yr v	
		mitted				Was V	/ater Well Disin	fected? C	YES	NO
5 TYPE OF CASIN	NG USED: 3. RPM (SR)	5. Wrought	Iron 7. Fibe	rglass	9. Ot	her (Specify	below) CAS	SING JOINTS: (	Glued	Threaded
2. PVC	4. ABS	6. Asbestos	s-Cement 8. Cond	crete tile	SDF	R-26			Welded	Clamped
Blank casing diameter	5 in	n. to	32 ft., Di	ia.	in.	to	ft.,	Dia. i	n. to	ft.
1	and surface:	12 in.,	Weigh	nt: 2.		s. / ft.				
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214  TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. S	Stainless Steel	5. Fiberglass	7. PVC	>	9. A	38	11. Ot	her (specify)		
2. Brass 4. (	Galvanized	6. Concrete T	ile 8. RMP	(SR)	10. As	sbestos-Cen	nent 12. No	one used (open l	hole)	
SCREEN OR PERFOR										
1. Continuous slot 3. Mill slot 5. Gauzed wrapped					7. Torch cut 9. Drilled holes 11. None ( open ho					open hole)
2. Louvered shutter	4. Key pur	nched 6. V	Wire wrapped		(8. Sa)	w cut	10. Oth	er (specify)		
SCREEN - PERFORAT	ION INTERVAL	From	<b>32</b> ft.	to	85	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACE	K INTERVALS:	From	<b>24</b> ft.	to	85	ft.,	From	ft.	to	ft.
L		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIA	LS: 1. Neat ce	ement	2. Cement Grou	t	3	. Bentonite		Other bente	onite hole pl	ug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to								ft.		
What is the nearest source of possible contamination:  1. Septic tank 4. Lateral lines 7. Pit privy					Livestocl	k pens	13. Insect	icide storage	15. Oil well/0	Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Ft						rage 14. Abandon water well 16. Other (specify below)				
③ Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage										
Direction from well?	East						How ma	any feet? 10 f		
From To		ITHOLOGIC	CLOG		From	То		LITHOLO	GIC LOG	
	opsoil :lav									
	ine sand									
	andstone									
	nedium sand									
39 85 8	rey shale			-						
						·		15 5 0 1 15 1		
				_						
								-		
	<del> </del>									
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and										
was completed on (mo/day/year) 7/15/2013 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/17/2013										
under the business name of Harp Well and Pump Service by (signature)  Todd S. Harp										