WATE	R WEI	LL RECORD	Form WV	VC-5	Division of Water	r Resources App. N	o. [144-13
1	CATION nty: Sed	OF WATER WELL:	Fraction NE ¼ SW ¼ SW	1/4 1/4	Section Number 27	Township No. T 26 S	Range Number R 1
		Address of Well Location; i		Global Positioning	System (GPS) in	nformation:	
from nearest town or intersection: If at owner's address, check here <b>[7]</b> .					Latitude: .37.754900 (in decimal degrees)		
3850 N. Hydraulic St., Wichita, KS 67219					Longitude: 97.314900 (in decimal degrees)		
					Elevation: .1332.2	<u>?0</u>	••••
2 WATER WELL OWNER: LISD 259 School Service Center					Datum: WGS 84	I, 🗹 NAD 83, 🗀	] NAD 27
COD 200 Control Control					Collection Method:  GPS unit (Make/Model:)		
RR#, Street Address, Box #: 3850 N. Hvdraulic St. City, State, ZIP Code : Wichita, KS 67219				☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey			
City	, State, Z	Wichita,	KS 6/219		Est. Accuracy:	3 m.	5-15 m.   >15 m
3 LOCATE WELL							
	H AN "X	" IN 4 DEPTH OF O	COMPLETED WELL				
SECT	TION BO						
	N	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr					
	Pump test data: Well water wasft. after hours pumping gpm						
<sub>N</sub>	EST. YIELDgpm. Well water was						
$ \mathbf{w} $							
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☑ Injection well							
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes V No							
S If yes, mo/day/yr sample was submitted							
		water wen dishi					
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter 1.5 in. to 17.5 ft., Diameter in. to ft., Diameter in. to ft.							
Casing height above land surface. 0. in., Weight 0.537. lbs./ft., Wall thickness or gauge NoSCH 40.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel     ☐ Stainless Steel     ☐ PVC     ☐ Other (Specify)       ☐ Brass     ☐ Galvanized Steel     ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From 17.5 ft. to 27.5 ft., From ft. to ft.							
From							
GRAVEL PACK INTERVALS: From16.5 ft. to27.5 ft., From ft. to ft.							
From							
6 GROUT MATERIAL: ☐ Neat cement							
Grout Intervals: From .1.9							
What is the nearest source of possible contamination:  ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage  ▼ Other (specify below)							
				Fuel storage			iei (specify below)
Sewer lines   Cesspool   Sewage lagoon   Fuel storage   Abandoned water went							
Direc	ction from	n well Northeast			rom well10 feet		
FROM	TO	LITHOLOG	IC LOG	FROM	TO LITHO. LO	OG (cont.) or PLU	JGGING INTERVALS
0	0.5	Asphalt					
0.5	5.0	Brown-black, CLAY, sa	ndy, damp				
5.0	21.6	Med. stiff, dk. brown-bri					
		silt, tr. sand, damp to m					
21.6	25.0	Med. dense, lt. grey-grr					-
		SILT, damp to moist, w					
25.0	27.1	Soft, It. grey to rusty, C					
		little-some silt, moist to					
27.1	27.5	Dense, dk. grey, SILTY		Ì			
		unweathered, wet					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged							
under m	y jurisdi	ction and was completed or	n (mo/day/year) .1.0/1.4	/2014 and	d this record is true t	o the best of my k	knowledge and belief.
Kansas	Water W	ell Contractor's License N	o7.27 This W	ater Well Re	cord was completed	on (mo/dav/vear)	11/13/2014
under th	ne busine	ss name ofVista Geosc	iences, LLC		by (signature)	John V Har	Die erwichen V. Fortang, er-Vista Geoöctence LLC, ou genalt-fortanne/VistaGeoöctence.com, cvUS
INSTRU	CTIONS:	Use typewriter or ball point pen	PLEASE PRESS FIRMLY	and <u>PRINT</u> clea	arly Please fill in blanks	and check the correct	answers. Send one copy to
Telenho		partment of Health and Environr					

http://www.kdheks.gov/waterwell/index.html

IW-13