WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE 1/4 NE 1/4 NW 1/4 6 Т 26 S R 1E E/W Distance and direction from nearest town or city street address of well if located within city? 4 construct on 1 permit VALLEY CENTER, CITY OF WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: P. O. Box 188 20150091 Valley Center, Kansas CITY, STATE: Application Number: ZIP CODE 35 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: **ELEVATION:** ft. ft. ft. Depth of groundwater Encountered: 12 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/1/15 Pump test data: Well water was ft. after hours of pumping @ gpm N₩ NE Est. Yield: apm Well water was ft. after hours of pumping @ gpm Ξ Bore Hole Diameter 12 to 35 ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 7. Lawn and garden only SW SE 3. Feedlot 5. Public water supply 12. Other (Specify below) 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) submitted Was Water Well Disinfected? NO TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: ( Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 8 20 Dia. Dia. to ft.. ft.. ft. to in. to 12 5.52 Casing height above land surface: in. Weight: lbs. / ft. Wall thickness or gauge No. .332 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 1 Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 2. Brass 4. Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 7. Torch cut 9. Drilled holes 3. Mill slot 5. Gauzed wrapped 11. None ( open hole) 1. Continuous slot 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 20 35 From to ft From to ft. ft. to From ft.. From ft ft to 20 **GRAVEL PACK INTERVALS:** ft. to 35 From ft.. From ft. to ft. From ft. to ft.. From ft. ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 0 ft 20 ft From ft. ft., From ft. to What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Apparent 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit How many feet? Direction from well? LITHOLOGIC LOG From Тο From Τо LITHOLOGIC LOG 0 topsoil 15 clay 3 15 fine sand 25 25 35 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 5/1/2015 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/6/2015 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb