	WATER WELL REC	ORD Form WW	/C-5 KSA 82	a-1212	
1 LOCATION OF WATER WELL:	FRACTION	SECT	TON NUMBER TO	WNSHIP NUMBER	RANGE NUMBER
Sedgwick	NE 1/4 NW 1/	4 NW 1/4	22 T	26 S	R 1E E/W
Distance and direction from nearest town or o	city street address of well if located within	n city?			
5245 N. Lakewood Hills	Park City, K	ansas			
	ES CONSTRUCTION				
	333 E. 21st N. SE#303			Board of Ag	riculture, Division of Water Resource
CITY, STATE: WI	chita, Kansas	ZI	P CODE:	Application Nu	mber:
	DEPTH OF COMPLETED WEL		ELEVA		
WITH AN "X" IN SECTION BOX:		-			
N III	Depth of groundwater Encountered			ft.	ft.
	WELL'S STATIC WATER LEVEL	25 FT. BELO	W LAND SURFACE	MEASURED ON mo/	/day/yr: 8/24/16
NW NE	Pump test data:	Well water was	ft. á	ifter hour	s of pumping @ gpm
	Est. Yield: gpm	Well water was	ft. a	after hour	rs of pumping @ gpm
м — Е	Bore Hole Diameter 12	in. to $1$	<b>20</b> ft. a	and in.	to ft.
	WELL WATER TO BE USED AS:			9. Dewater	ing 11. Injection well
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)					
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well					
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample					
	submitted		Was Water We	ell Disinfected?	YES NO
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass 9. O	ther (Specify below)	CASING JOINTS:	Glued Threaded
1. Steel 3. RPM	(SR)	- 501	R76		Welded Clamped
2. PVC 4. ABS	6. Asbestos-Cement	8. Concrete tile SD	120		
Blank casing diameter 5	in. to <b>35 ft.,</b>	Dia. in.	to ft.	Dia.	in. to ft.
Casing height above land surface:	12 in.,	Weight: 2.35 II	os. / ft.	Wall thickness or gau	ige No214
TYPE OF SCREEN OR PERFORATION MATERIAL:   1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)					
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot 3. Mill	slot 5. Gauzed wrap	ped 7. To	rch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key	y punched 6. Wire wrappe	d (8. Sa	w cut	10. Other (specify)	
		100			
SCREEN - PERFORATION INTERVA	L From 35 ft.	to 120	ft., Fror	n ft.	to ft.
	From ft.	to	ft., Fror	n ft.	to ft.
GRAVEL PACK INTERVALS	: From <b>24</b> ft.	to 120	ft., From	n ft.	to ft.
	From ft.	to	ft., Fror	n ft.	to ft.
			-	•••	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug					
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well					
1. Septic tank 4. Lateral lines 4. Lateral lines 4. Lateral lines					
2. Sewer lines 5. Cess Pool					
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well? West				How many feet? 10	
From To	LITHOLOGIC LOG	From	To	LITHOL	OGIC LOG
0 3 topsoil					
3 12 clay					
12 28 very fine sa	and				
28 120 grey shale					
			ļ		
			<b>├</b> ───		
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and					
	8-24-16 ar	nd this record is true to the	-	-	E/0.01 (
Kansas Water Well Contractor's Lic	8-24-16 ar		-	(day/year) 8/2	5/2016 S. Harb