1 LOCATION OF WATER WELL: FRACTION Section Number Township Num	mber Range Number		
	1 1 12		
Sedqwick SW 1/4 NE 1/4 SW 1/4 7 T 26 Distance and direction frem nearest town or city street address of well if located within city?	S I R IE E	Z/W	
6431 Bella Road Wichita, Kansas			
WATER WELL OWNER: BOEKEN, Wilber	Lead to the District Property of the Property		
RR#, ST. ADRESS, BOX#: 6431 Bella Road Board of Agriculture, Divivision of Water Resource			
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:			
LOCATE WELL'S LOCATION WITH DEPTH OF COMPLETED WELL 40 ft. ELEVATION:	·		
Depth(s) groundwater Encountered 1 nt. 2	ft. 3	ft.	
WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED	ON mo/day/yr 05/04/19	98	
Pump test data: Well water was ft. after	hours pumping	gpm	
Est. Yield gpm: Well water was ft. after	hours pumping	gpm	
Bore Hole Diameter 12 in. to 40 ft. and	in. to	ft.	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning	g 11 Injection well		
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering	12 Other (Specify below	1)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	1		
	🗶 ; If yes, mo/day/yr sample was	8	
S submitted Water Well Disinfecte	ed? Yes X No		
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JC	OINTS: Glued X Clamped		
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below)	Welded		
2 PVC 4 ABS 7 Fiberglass SDR-26	Threaded		
Blank casing Diameter 5 in. to 30 ft., Dia in. to ft., Dia	in. to ft.		
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or	gauge No 214		
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 A	As bestos-cement		
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11	other (specify)		
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12	None used (open hole)		
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut	11 None (open h	ole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	s		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
/ Total cut	•	ft.	
1	ft. to		
from ft. to ft., From GRAVEL PACK INTERVALS: from 24 ft. to 40 ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24 ft. to 40 ft., From ft. to ft., From	ft. to ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug			
Chart Intervals From A	-	-	
What is the nearest source of possible contamination: 10 Livestock pens	ft. to 14 Abandon water well	ft.	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage	16 Other (specify below	ሳ	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent			
Direction from well? How many feet?			
	GGING INTERVALS		
0 6 topsoil			
6 10 clay			
10 25 medium sand			
25 40 medium coarse sand	* * * * * * * * * * * * * * * * * * *		
	,		
	THE TOTAL PROPERTY OF THE PARTY		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and			
was completed on (mo/day/year)			
Well Contractor's License No	05/05/98		
Under the business name of Harp Well & Pump Service. Inc by (signature)			
Todd S. Harp			