

1 LOCATION OF WATER WELL: County: <b>SEDGWICK</b>		Fraction <b>NW 1/4 NE 1/4 NE 1/4</b>	Section Number <b>17</b>	Township Number <b>T 26 S</b>	Range Number <b>R 1 E</b>
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: RR#, St. Address, Box # : <b>CITY OF PARK CITY 6110 NORTH HYDRAULIC ST.</b> City, State, ZIP Code : <b>WICHITA, KANSAS 67218-2499</b>			Well No. <b>2 - OFFSET</b> Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <b>44</b> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <b>17</b> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <b>17</b> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield <b>300</b> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <b>36</b> in. to ft., and in. to ft. WELL WATER TO BE USED AS: <b>5 Public water supply</b> 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <b>X</b> No; If yes, mo/day/yr sample was submitted <b>1-28-98</b> Water Well Disinfected? Yes <b>X</b> No			
		5 TYPE OF BLANK CASING USED:			
		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <b>Steel</b> 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter <b>18</b> in. to <b>34</b> ft. Dia <b>70.59</b> in. to ft. Dia in. to ft. Casing height above land surface <b>24</b> in. weight <b>70.59</b> lbs./ft. Wall thickness or gauge No. <b>0.375</b>			
		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel <b>3 Stainless steel</b> 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot <b>5 Gauzed wrapped</b> 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched <b>6 Wire wrapped</b> 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		SCREEN-PERFORATED INTERVALS: From <b>34</b> ft. to <b>44</b> ft. From ft. to ft. GRAVEL PACK INTERVALS: From <b>20</b> ft. to <b>44</b> ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <b>0</b> ft. to <b>20</b> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) <b>INDUSTRIAL AREA</b> Direction from well? <b>EAST</b> How many feet? <b>2500'</b>					
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS	
0	7	DARK BROWN SILTY CLAY			
7	12	MED. SILTY CLAY			
12	13	MED. BROWN CLAYEY SILT			
13	18	MED. BROWN FINE/MED SAND			
18	20	MED. BROWN FINE/MED. SAND			
20	28	MED. BROWN MED. SAND			
28	30	DARK GRAY CLAY			
30	33	MED. BROWN MED COARSE SAND			
33	38	MED COARSE SAND			
38	40	COARSE SAND & GRAVEL			
40	42	COARSE SAND & GRAVEL			
42	42.5	WELLINGTON SHALE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <b>(1) constructed</b> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>1-28-98</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>581</b> This Water Well Record was completed on (mo/day/yr) <b>2-16-98</b> under the business name of <b>LAYNE WESTERN</b> by (signature) <i>[Signature]</i>					