1 LOCATION OF WATER WELL:	FRACTION	water Well Record	rom wwc-	Section Number	Township Number	Range Number	
Sedgwick	NE 1/4	NE 1/4 I	NW 1/4	18	26	1 12	
·			1/4		T 26 S	l R 12 E/W	
Distance and direction from nearest town or city street address of well if located within city?							
6115 Bella Rd. Wichita, Kansas							
L-1	N, Marilyn					_	
RR#, ST. ADRESS, BOX #: 6115 Bella Rd. Board of Agriculture, Divivision of Water Resource							
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:						r:	
LOCATE WELL'S LOCATION WITH 4	DEPTH OF 🙉	MAGE CONVELL	41	ft. El	LEVATION:		
AN "X" IN SECTION BOX:	Depth(s) groundv	rater Encountered	1	ft.	2 ft.	3 ft.	
	VELL'S STATIC V	ATER LEVEL 18	3 гт	. BELOW LAND S	URFACE MEASURED ON mo/day/yr	05/08/1998	
	Pump tes	t data: Well	water was	ft.	after hours pum	ping gpm	
NWNE	st. Yield	gpm: Well	water was	ft.	after hours pum		
В	ore Hole Diameter)		to	ft.	and in.	to ft.	
"	ELL WATER TO		5 Public wate			njection well	
1 Mile Y	1 Domestic	3 Feedlot	6 Oil field wa		-	Other (Specify below)	
3W	2 Irrigation	4 Industrial	7 Lawn and		10 Monitoring well		
	-	arialagical cample s	•	•		o/day/yr sample was	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted water Well Disinfected? Yes X No							
5 TYPE OF CASING USED:	Subiliteed						
1 Steel 3 RMP (SR)		5 Wrought iron 6 Asbestos-Ceme		Concrete tile Other (Specify	- •	łued Clamped Velded	
5 Iuiii (51t)		7 Fiberglass	, in ,	Outer (Specify	- ·	hreaded X	
		<u> </u>			_		
Blank casing Diameter 1 1/4 in Casing height above land surface 26	n. to	ft., Dia	in.		ft., Dia in.	to ft.	
TYPE OF SCREEN OR PERFORATI	in. , On Material :	weight	,	lbs. / ft. 7 PVC	Wall thickness or gauge No. 10 Asbestos-ceme	ent	
5 Fiboneless 9 DMD (SD)							
1 Steel 3 Stainless Steel 5 Fiberguass 6 RWF (SR) 11 other (specify) N/A 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						,	
				AUG	8 Saw cut	•	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed w							
1 Continous slot 3 Mill slot 6 Wire wrappe					9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) N/A					A		
SCREEN-PERFORATION INTERVA	LS: from	ft.	to	ft., Fro	m ft. to	ft.	
from		ft.	. to	ft., From ft. to		ft.	
GRAVEL PACK INTERVALS: from		n	. to	ft., From ft. to		ft.	
from		<u>ft</u>	. to	ft., Fro	From ft. to ft.		
6 GROUT MATERIAL: 1 Neat cer	ment 2_0	Cement grout	3 Be	ntonite	4 Other bentonite h	ole plug	
Grout Intervals: From 2 ft. to 8		ft. From			ft. From 8	ft. to 18 ft.	
What is the nearest source of possible contamination:					bandon water well		
1 Septic tank 4 Lateral lines		7 Pit privy			fuel storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool					rtilizer storage 16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent						Apparent	
Direction from well? How many feet?							
FROM TO LITHOLOGIC LOG			FROM	ТО			
			0	2	surface silt and c	lay	
		2	8	cement grout			
			8	18	bentonite hole plu		
			18	41	chlorinated sand a	nd gravel	
		·		_			
		·			<u> </u>		
				1			
				1			
				11			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)	05/08/1	998			the best of my knowledge and		
Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr). 05/11/98							
Under the business name of Hard Well & Pump Service, Inc. by (signature)							
				, ,	Todd S	. Harp	