

1 LOCATION OF WATER WELL: <b>Sedgwick</b>	FRACTION <b>SE NW SE SE</b> <b>NE 1/4 SE 1/4 E 1/4</b>	Section Number <b>18</b>	Township Number <b>T 26 S</b>	Range Number <b>R 1E E/W</b>
--	--	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?


**5490 N. Sullivan Wichita, Kansas**

WATER WELL OWNER: **BABB, Vicki**  
 RR#, ST. ADDRESS, BOX #: **5490 N. Sullivan**  
 CITY, STATE, ZIP CODE: **Wichita, Kansas**

Board of Agriculture, Division of Water Resource

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF ~~CONCRETE~~ WELL **27** ft. ELEVATION:  
 Depth(s) groundwater Encountered **1** ft. **2** ft. **3** ft.

WELL'S STATIC WATER LEVEL **12** FT. BELOW LAND SURFACE MEASURED ON **09/21/1998**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter ~~unknown~~ in. to ft. and in. to ft.WELL WATER TO BE USED AS: **5** Public water supply **8** Air conditioning **11** Injection well**1** Domestic **3** Feedlot **6** Oil field water supply **9** Dewatering **12** Other (Specify below)**2** Irrigation **4** Industrial **7** Lawn and garden only **10** Monitoring wellWas a chemical/bacteriological sample submitted to Department? Yes No **X**; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes **X** No

5 TYPE OF CASING USED:	1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS:	Glued	Clamped
	2 PVC	4 ABS	6 Asbestos-Cement	9 Other (Specify below)		Welded	
			7 Fiberglass			Threaded	<b>X</b>

Blank casing Diameter **1 1/4** in. to ft., Dia in. to ft., Dia in. to ft.Casing height above land surface **36** in., weight lbs. / ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	11 other (specify)	<b>N/A</b>
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	

SCREEN OR PERFORATION OPENING ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: from ft. to ft., From ft. to ft.

from ft. to ft., From ft. to ft.

from ft. to ft., From ft. to ft.

from ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other **bentonite hole plug**Grout Intervals: From **0** ft. to **3** ft. From ft. to ft. From **3** ft. to **27** ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? None Apparent

How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 3 cement grout

3 27 bentonite hole plug

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **09/21/1998** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **236** This Water Well Record was completed on (mo/day/yr) **09/25/98** Under the business name of **Harp Well & Pump Service, Inc.** by (signature)

Todd S. Harp