

MW-16R

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NW 1/4 SE 1/4	27	T 26 S	R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? 2400 E. 37th STREET N. WICHITA, KS					
2 WATER WELL OWNER: PHILLIPS PIPE LINE COMPANY		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 370 ADAMS BUILDING		Application Number:			
City, State, ZIP Code: BARTLESVILLE OK 74004					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 22.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 4 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr 5-13-98			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 1/4 in. to 22.5 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No <input checked="" type="checkbox"/>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded <input checked="" type="checkbox"/>			
Blank casing diameter 2 in. to 4.0 ft. Dia.		in. to ft. Dia.			
Casing height above land surface 36 in. weight		lbs./ft. Wall thickness or gauge No. Sch 80			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
SCREEN-PERFORATED INTERVALS: From 19 ft. to 4 ft.					
GRAVEL PACK INTERVALS: From 22.5 ft. to 3 ft.					
6 GROUT MATERIAL:		3 Bentonite 4 Other Conc.			
Grout Intervals: From 3 ft. to 2 ft.		From 2 ft. to Surface ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? South		How many feet? 150'			
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS	
0.0	4.0	brn. clay			
4.0	9.0	wet brn. clay			
9.0	14.0	brn sandy clay			
14.0	22.5	olive shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-12-98 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 614 This Water Well Record was completed on (mo/day/yr) 6-15-98					
under the business name of MAXIM TECHNOLOGIES, INC by (signature) <i>William Steffens</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4