LOCA	TION OF W	ATPD WELL.	FRACTION	Water Well Reco	rd Form WWC-5	Section Number		Danes Number
LOCATION OF WATER WELL:				NT-7	NT		Township Number	Range Number
Sedgwick Distance and direction from present town or city of season			SW 1/4		NW 1/4	29	т 26 в	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?								
4400 N. Seneca Wichita, Kansas WATER WELLOWNER: WESTERN RESOURCES								
LI WEDIEM KEDOOKOED								
F.O.BOX 200								
T					2.6	67201	Application Number	r:
	TE WELL'S I " IN SECTIO			MPLETED WELL	36	ft. ELE	VATION:	3 ft.
1 +		- N	Depth(s) groundw		1		2 ft. FACE MEASURED ON mo/day/yr	
			WELL'S STATIC W	_	. •		-	01/15/1998
Pump test data: Well water was ft. after hours pumping gpm								
≅		l i	Est. Yield	91	water was		nfter hours pum	
13 M	/	1.5	Bore Hole Diameter WELL WATER TO	12 in.	to 36	ft.	and in.	to ft.
1			1 Domestic	3 Feedlot	5 Public wate		•	njection well Other (Specify below)
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify be 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							outer (specify below)
II	A Market							
'	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted							
TUBE OF CASING LISED.								
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 9 Other (Specify below) Welded								
2 PVC		4 ABS		7 Fiberglass	•	DR-26	•	'hreaded
Blank casing Diameter 5 in. to 23 ft., Dia in. to ft., Dia in. to ft.								
	_	ve land surface 12		•		•••	Vall thickness or gauge No.	.214
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
	nous slot	3 Mill slot			e wrapped		9 Drilled holes	(- F)
27 amount desired								
SCHEN DEDENDATION INTERVALS.								
SCREE	N-I ERFO	RATIONINIERVA	23		t. to 31	ft., From	ft. to	ft.
from				-	ft. to ft., From		ft. to	ft.
	GRAVEL PACK INTERVALS: from 23				ft. to 36 ft., From		ft. to	ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bent on ite hole plug								
Grant Intervals: From 2								
		t source of possible o		ft. From	ft. From ft. to 10 Livestock pen		ft. From k nens	ft. to ft. bandon water well
1 Septic tank 4 Lateral lines				7 Pit privy 11 Fuel stora			a 4 1 gamma on 11 and 11 on	
2 Sewer lines 5 Cess pool				• •			storage 15 Oil well/Gas well tilizer storage 16 Other (specify below)	
ı	rtight sew	-			9 Feedyard 13 Insecticide st			outer (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecuciae storage Direction from well? Northeast How many feet? 50								
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								RVALS
0	4	topsoil						
4	8	clay						
8	18		parse sand					
18	20	very red	sand					
20	28	medium sa						
28	36	medium fi	ine sand				DEACI	VED
							RECE	VEU
								1009
							့)	1998
							BUREAU OF	WATER
							DOI (E/10-01	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well C	ontractor	's License No	236	This Water Well I	Record was c	ompleted on (mo	/day/yr)	
Under the business name of HarpWell&PumpServiceInc by (signature)								
Todd S. Harp								