l leas			Lancatas	Water Well Record	Form WWC-5	KSA 82a-1212			
1 LOCATION OF WATER WELL:			FRACTION			Section Number	Township Number	Range Number	
			NW 1/4		SE 1/4	31	т 26 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?									
3349 N. Coolidge Wichita, Kansas									
WATER WELL OWNER: PORTER, Farrell									
	#, ST. ADRES		N. Coolid				Board of Agriculture, Di	vivsion of Water Resource	
	ry, state, z		ta, Kansa				Application Number		
	ATE WELL'S X" IN SECTI	LOCATION WITH 4	DEPTH OF COM		42		VATION:	_	
	-	N	Depth(s) groundwa		. 1	ft.	2 ft.	3 ft.	
		W	VELL'S STATIC WA		•		FACE MEASURED ON mo/day/yr	08/13/1998	
'	NW	NE	Pump test		vater was		ifter hours pum		
<b>a</b>			st. Yield	91	water was		after hours pum		
1Mile	w	Y : 121	ore Hole Diameter	12 in.	to 42	ft.	and in.	to ft.	
		"	ELL WATER TO E  1 Domestic		5 Public water 6 Oil fleld wat		•	njection well Other (Specify below)	
1 1	sw	··	2 Irrigation				Monitoring weli	dier (specify below)	
2 migazon / 2 mingazon / 2 ming						ū	-/d/		
Was a chemical/bacteriological sample submitted to Departs submitted							artment? Yes No X ; If yes, mo/day/yr sample was Water Well Disinfected? Yes X No		
5 T	YPE OF C	ASING USED:	завинев						
I Ste		3 RMP (SR)		5 Wrought iron 6 Asbestos-Cemer		Concrete tile Other (Specify be	<b>U</b>	lued X Clamped elded	
2 PV	/C	4 ABS		7 Fiberglass	-	OR-26	,	eiueu hreaded	
	casing Dia		ı. to 32	ft., Dia				_	
	_	ove land surface 12		weight 2	in. 35	to lbs. / ft. \	ft. , Dia in. Vall thickness or gauge No.	to ft.	
		EN OR PERFORATION		weight Z		PVC	10 As bestos-ceme		
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open ho								en hole)	
SCRE	EN OR PI	ERFORATION OPEN	ING ARE:	5 Gauz	ed wrapped		8 Saw cut	11 None (open hole)	
1 Cont	tinous slot	3 Mill slot			wrapped		9 Drilled holes		
2 Louv	ered shutt	ter 4 Key punc	ched	7 Torch	cut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 32 ft. to 42 ft., From ft. to ft.									
from ft. to ft., From ft. t								ft.	
GRAVEL PACK INTERVALS: from 24				ft. to 42		ft., From		ft.	
<u> </u>			from	ft.	to	ft., From	ft. to	n.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From							ft. From	ft. to ft.	
What is the nearest source of possible contamination:						10 Livestoc		bandon water weli	
1 Septic tank 4 Lateral lines			ines	7 Pit privy		11 Fuel sto	130	il well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertilizer storage		ther (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? East How many feet? 20 FROM TO LITHOLOGIC LOG FROM TO PLUCCINC INTERVALS								******	
0	2	topsoil	THOLOGIC LOG		FROM	ТО	PLUGGING INTER	VALS	
2	10	fine sand	******			<del> </del>			
10	15	clay				<del> </del>			
15	28	coarse sa	nd			+ +			
28	32	clay				<b> </b>			
32	42	medium co	arge gand		<u> </u>	1	<u>,,                                     </u>		
		THOUSE CO.	arbe band						
					1				
								•	
							***************************************		
					1				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Well Contractor's License No236									
Under the business name of HarpWell& PumpServiceInc by (signature)									
						3	Todd S	. Harp	