Licc	ATION OF W	ATER WELL:	FRACTION	Water Well Rec				
الم			//\	N SE NW S		Section Number	Township Number	Range Number
Sedgwick WE			NM 1/4	839 1/4	31	T 26 s	R 1E E/W	
Distance and direction from nearest town or city street address of well if located within city?								
3249 Carlock Wichita, Kansas								
WATER WELL OWNER: BENTLEY, Jean								
RR#, ST. ADRESS, BOX#: 3249 Carlock Board of Agriculture, Divivsion of Water Resource								
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:								
		LOCATION WITH	4 DEPTH OF COM	MPLETED WELL	40	ft. EI	LEVATION:	
AN "	" IN SECTIO	N BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.
WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON 1000 day/yr O							05/07/1998	
Pump test data: Well water was ft. after hours pumping								
Ret Vield gam: Wall water was & offen house annual							. Br	
N Mile			Bore Hole Diameter	12 in.	to 40	ft.	and in.	to ft.
\(\frac{1}{2}\) \(\frac{1}{2}\)	' X	I I	WELL WATER TO		5 Public water			njection well
l			1 Domestic	3 Feedlot	6 Oil field wa		•	njection wen Other (Specify below)
	sw	SiE	2 Irrigation	4 Industrial	7 Lawn and g		10 Monitoring well	outer (Specify below)
			·				•	
'	<u> </u>	S	Was a chemical/bacte	eriological sample	submitted to De	-		io/day/yr sample was
submitted Water Well Disinfected? Yes X No								
_				5 Wrought iron		Concrete tile		lued X Clamped
1 Ste		3 RMP (SR)		6 Asbestos-Cen	nent 9	Other (Specify	•	Velded
2 PV	_	4 ABS		7 Fiberglass	S	DR-26	Т	'hreaded
Blank casing Diameter 5 in. to 2.5 ft., Dia in. to ft., Dia in. to ft.								
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No. 214								
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
1 Cont	inous slot	3 Mill sl	lot		re wrapped		9 Drilled holes	
2 Louv	ered shutte	r 4 Key p	unched	7 Tot	rch cut		10 Other (specify)	
SCREE	N-PERFO	RATION INTERV	VALS: from 25		ft. to 35	2 F		•
]			23			ft., Fro		ft.
from GRAVEL PACK INTERVALS: from 2.4					ft. to	ft., Fro		ft.
1	GRAV	EL PACK INTER		ft. to 40		ft., Fro		ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hent on its hole of								ft
Count Internals. P. A. Deliconities note plug								
What is the propert course of results contained and								ft. to ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines				5 PM - 1		10 Livest		bandon water well
· 4 Lauci at Inics			7 Pit privy		11 Fuel s	150	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon			lizer storage 16 C	Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent								
Direction from well? How many feet?								
FROM TO LITHOLOGIC LOG FROM TO PLUCCINC INTERVALS								RVALS
0 4	4	topsoil						
4	8	clay						
8	15	medium s	and					
15	40	very coa	rse gravel					
							A CONTRACTOR OF THE CONTRACTOR	
								7
						1 1		
						 		
						 -		
	 					+ +		
						 		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No236								
Under the business name of HarpHell&PumpServiceInc by (signature)								
							Todd S	. Harp
								,