KOLAR Document ID: 1412920

			WWC-5		vision of Water		W 11 TD		
			ge in Well Use		ources App. No.		Well ID		
1 LOCAT	rion of V _{y:} Sedgwic	VATER WELL: k	Fraction NW ¼ NE ¼ SW ¼		ction Number	Township Number T 26 S	Range Number R 1 ☑ E □ W		
2 WELL OWNER: Last Name: BROCKUS First: BRYAN Business: BRYAN BROCKUS Address: 3159 N CARLOCK AVE Address:									
City:	WICHITA	State: KS	ZIP: 67205		1				
	3 LOCATE WELL 4 DEPTH OF COMPLETED WELL:40.					ft. 5 Latitude: 37.741208 (decimal degrees)			
li .	SECTION ROX. Depth(s) Groundwater Encountered: 1)!					Edit Grade :			
1	2)					Datum: ☐ WGS 84 ☑ NAD 83 ☐ NAD 27 Source for Latitude/Longitude:			
		☐ below land surface	below land surface, measured on (mo-day-yr)						
NW	above land surface, measured on (mo-day-yr). 4/12/20 Pump test data: Well water was					(WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper:			
w									
'	, , ,	Well	Well water was ft.						
3₩	-XSE	after hours pumping			6 Elevation:1351				
<u> </u>	S								
1 r			in. to	., ft.		Other KOLAR			
7 WELL WATER TO BE USED AS:									
1. Domestic: ☐ House		5. ☐ Public Water Supply: well ID							
_	Lawn & Garden 7. Aquifer Recharge: well ID								
☐ Livesto	Livestock 8. Monitoring: well ID					12. Geothermal: how many bores?			
	☐ Irrigation 9. Environmental Remediation: well ID					a) Closed Loop ☐ Horizontal ☐ Vertical b) Open Loop ☐ Surface Discharge ☐ Inj. of Water			
3. ☐ Feedlo		☐ Air Sparg ☐ Recovery		extraction	b) Open	Loop Surface Discl	harge Inj. of Water		
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☑ No If yes, date sample was submitted:									
8 TYPE OF CASING USED: Steel ZIPYC Steel CIPYC Steel CASING JOINTS: ZI Glued Steel Clamped Steel Cla									
Casing diameter									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☑ PVC ☐ Other (Specify)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous Slot ☑ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)									
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)									
SCREEN-PERFORATED INTERVALS: From .20 ft. to .40 ft., From									
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to 24 ft., From ft. to ft. to ft.									
Nearest sou	rce of possit	le contamination:							
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage									
□ Sewer Lines □ Cess Pool □ Sewage Lagoon □ Fuel Storage □ Abandoned Water Well □ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well									
Other (Specify)									
Direction from well?ft.									
10 FROM	TO	LITHOLOG	GIC LOG	FROM	TO LI	THO. LOG (cont.) or P	LUGGING INTERVALS		
3	3 14	TOPSOIL CLAY		1	 				
14	19	FINE SAND		 	 				
19	40	COARSE							
				Notes:					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\big \) constructed, \(\big \) reconstructed, or \(\big \) plugged									
under my jurisdiction and was completed on (mo-day-year) .4/12/2018 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 611 This Water Well Record was completed on (mo-day-year) 5/2/2018									
under the business name of Chase Drilling. Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.									
KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.									
		eks.gov/waterwell/index.html					KSA 82a-1212		