


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NE 1/4 NE 1/4	SECTION NUMBER 35	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1E E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
4501 E. 37th St. N. Wichita, Kansas

2	WATER WELL OWNER: KOCH INDUSTRIES	Board of Agriculture, Division of Water Resource
	RR#, ST. ADDRESS, BOX #: 4111 E. 37th St. N.	Application Number:
	CITY, STATE: Wichita, Kansas	ZIP CODE:

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4	DEPTH OF COMPLETED WELL: 85 ft. ELEVATION:
	Depth of groundwater Encountered:		
	WELL'S STATIC WATER LEVEL	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr: 12/18/18
	Pump test data:	Well water was	ft. after hours of pumping @
	Est. Yield:	gpm	Well water was
	Bore Hole Diameter	in. to	ft. and in. to
	WELL WATER TO BE USED AS:		
	1. Domestic	3. Feedlot	5. Public water supply
	2. Irrigation	4. Industrial	6. Oil field water supply
	7. Lawn and garden only	8. Air conditioning	9. Dewatering
	10. Monitoring well	11. Injection well	12. Other (Specify below)
	Was a chemical/bacteriological sample submitted to Department?	NO	If yes, what mo/day/yr was sample submitted
	Was Water Well Disinfected?	YES	NO

5	TYPE OF CASING USED:	1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS:	Glued	Threaded
		2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	Welded	Clamped	
	Blank casing diameter	6 in.	to	ft.	Dia.	in.	to	ft.	Dia.
	Casing height above land surface:	60 in.	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.	.214			
	TYPE OF SCREEN OR PERFORATION MATERIAL:								
	1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)			
	2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)			
	SCREEN OR PERFORATION OPENINGS ARE:								
	1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)			
	2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)				
	SCREEN - PERFORATION INTERVAL	From	ft.	to	ft.	From	ft.	to	ft.
	GRAVEL PACK INTERVALS:	From	ft.	to	ft.	From	ft.	to	ft.

6	GROUT MATERIALS:	1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug
	Grout intervals:	From 5 ft.	to 85 ft.,	From	ft.	to
	What is the nearest source of possible contamination:					
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage		
	Direction from well?					How many feet?

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
			0	5	compacted soil
			5	85	bentonite hole plug

7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 12/18/18 and this record is true to the best of my knowledge and belief.
	Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/19/18
	under the business name of Harp Well and Pump Service by (signature) Todd S. Harp