	WATER WELL RE	CORD Fo	orm WW	C-5 KS	SA 82a-1212			
1 LOCATION OF WATER WELL:	FRACTION		SECTI	ON NUMBER	TOWNSHIP NUN	IBER	RANGE NUMB	R
Sedgwick	SE 1/4 NW	1/4 <b>NW</b>	1/4	34	T 26	s	R 1E	E/W
Distance and direction from nearest town or c	tity street address of well if located w	ithin city?						
3608N Crest Ct.	Wichita, Kansas							
	BL CONSTRUCTION							
	42 W. 21st N	•			B	oard of Agricu	Iture, Division of Water	Resource
			-	CODE: 67	205	lication Numb		
	chita, Kansas	0.0		CODE: 07		lication Numb		
	DEPTH OF COMPLETED W	ELL: 90	ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX:	 Depth of groundwater Encounte	red:	ft.			ft.		ft.
	WELL'S STATIC WATER LEVE	≡L <b>30</b>	ET BELOV		RFACE MEASURED	ON mo/da	v/vr: 9/9/19	
	Pump test da				ft, after		of pumping @	gpm
					ft. after		of pumping @	gpm
E N	01	Well wate	to 9	n "				ft.
			10 9	D ft.	and	in.	to	
∽ - SW SE	WELL WATER TO BE USED A	S: 5 Bublic wate		7 Jawn a	nd garden only 9	Dewatering	•	
	1. Domestic 3. Feedlot					Monitoring	12. Other (Speci	ty below)
	2. Irrigation 4. Industria						hat mo/day/yr was:	ample
S	Was a chemical/bacteriological sai submitted	mple submitted to De	epartment?	YES Was W	ater Well Disinfecte		YES) NO	
							~	
5 TYPE OF CASING USED: 1. Steel 3. RPM	(SP) 5. Wrought Iron	7. Fiberglass	9. Oth	ner (Specify	below) CASING			readed
	6. Asbestos-Cement	8. Concrete tile	, SDR	R-26		1	Welded Cla	mped
2. PVC 4. ABS								
Blank casing diameter 5	in. to <b>30 ft.</b> ,	, Dia.	in.	to	ft., Dia.	in	. to	ft.
Casing height above land surface:	12 in.,	Weight:	2.35 lb	<b>s</b> . / ft.	Wall thickne	ess or gauge	No214	
TYPE OF SCREEN OR PERFORATI	ON MATERIAL:	-						
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)								
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
		· · ·						
SCREEN OR PERFORATION OPEN							44 Nama ( aman	
1. Continuous slot 3. Mill	slot 5. Gauzed w	rapped	7. Tor	ch cut	9. Drilled h	oles	11. None ( oper	noie)
2. Louvered shutter 4. Key	y punched 6. Wire wrap	ped	8. Sav	v cut	10. Other (s	pecify)		
SCREEN - PERFORATION INTERVA	L From 30	ft. to	90	ft.,	<b>F</b>			<i>c</i> ,
Solecid - FERFORATION INTERVA			90		From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS	E From 24	ft. to	90	ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
				Dentenite	Oth	er honto	nite hole plug	
Grout Intervals: From What is the nearest source of possible		ft., From	ft.	to	ft., F	rom	ft. to	ft.
1	7 Dit priva	, 10	. Livestoci	k pens	13. Insecticide	storage	15. Oil well/Gas	well
1. Septic tank 4. Lateral lines 11 Fuel starses (14. the tank of the second sec								v below)
2. Sewer lines 5. Cess Pool								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well? South					How many f			
From To	LITHOLOGIC LOG		From	То	L	THOLOG	GIC LOG	
0 3 topsoil								
<u>3 8 clay</u>								
8 52 brown shal	e							
52 90 gray shale								
7 Contractor's or Landowner's Co	rtification: This water well was	1 constructed	2 10	constructed	or 3, plug	ged u	nder my jurisdiction	and
was completed on (mo/day/year) 9/9/19 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/11/19								
under the business name of Harp Well and Pump Service by (signature) Todd S. Hourb								