

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

SW NW NW SW

22
32

1. Location of well:		County	Fracture	Section number	Township number	Range number
JEDGWICK		1/4	1/4	1/4	32	T 26 S R 1E E/W
2. Distance and direction from nearest town or city:				3. Owner of well: J.R. WHEELER		
Street address of well location if in city: 3330 N HOOD - WICHITA KS				R.R. or street: 3330 N HOOD		
4. Locate with "X" in section below:				City, state, zip code: WICHITA KS		
Sketch map:				6. Bore hole dia. 8 in. Completion date 4-16-76		
BORED 8" HOLE TO 10' THEN 6" TO 21 FT. USED SAND BUCKET TO COMPLETION AT 35 FT.				Well depth 35 ft.		
5. Type and color of material				7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary		
TOP SOIL BLACK 0 2.5				8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other		
DIRT SOME CLAY BROWN 2.5 4.5				9. Casing: Material Height: Above or below Threaded Welded Surface 17 in. RMP PVC Weight 1.55 lbs./ft.		
CLAY SANDY BROWN 4.5 7.0				Dia. 5 in. to 35 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 0.200		
SAND MEDIUM RED BROWN 7.0 9.0				10. Screen: Manufacturer's name SUN FLOWER		
SAND FINE TAN 9.0 12				Type RMP Dia. 5 in. Slot gauge 0.31 Length 8 ft. Set between 28 ft. and 35 ft. Gravel pack? No size range of material		
CLAY GRAY 12 13				11. Static water level: mo./day/yr. 21 ft. below land surface Date 4-16-76		
SAND MED. TAN 13 17				12. Pumping level below land surfaces: ft. after hrs. pumping NA g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 100 g.p.m.		
GRAVEL COARSE BROWN 17 20				13. Water sample submitted: mo./day/yr. Yes No Date		
GRAVEL VERY COARSE REDDISH 20 24.5				14. Well head completion: Pitless adapter 12 inches above grade		
CLAY GRAY 24.5 25				15. Well grouted? YES With: Neat cement Bentonite Concrete Depth: From 0 ft. to 10 ft.		
SAND COARSE LT. BROWN 25 28.5				16. Nearest source of possible contamination: ft. 75 Direction SE Type SEWER LINE Well disinfected upon completion? Yes No		
GRAVEL MEDIUM LT. BROWN 28.5 35				17. Pump: Not installed Manufacturer's name PFW Model number HP 175 Volts 110 Length of drop pipe 27 ft. capacity 18 g.p.m. Type: Submersible Turbine Jet TWIN PIPE Reciprocating Centrifugal Other		
CLAY BLUE GRAY - FINISH -				18. Elevation: 1300 Topography: Hill Slope Upland Valley 19. Remarks:		
(Use a second sheet if needed)				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDED PUMP WELLS Business name License No. 1094 Address 5111 MEYER RD WICHITA KS Signed D. L. Beardsley Date 5/8/76 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5