Est. Yield gpm: Well water was fit gpm: Well water was fit gpm: Well water was fit gpm: Well water supply sw sk .	Board of Agriculture, Division of Water Resource Application Number: EVATION: ft. 2.
WATER WELL OWNER: WATER WELL OWNER: PR#, St. Address, Box # Ity, State, ZIP Code LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL. # ft. below land Pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner was free borner with the pump test data: Well water was free borner with the pump test data: Well water was free borner was free born	Board of Agriculture, Division of Water Resource Application Number: EVATION: ft. 2.
At St. Address, Box #: At State, ZIP Code LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL. AN "X" IN SECTION BOX: WELL'S STATIC WATER LEVEL. Pump test data: Well water was fit bore hole Diameter. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 2 Irrigation 4 Industrial 7 Lawn and garden only was a chemical/bacteriological sample submitted to Department? mitted TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC) 4 ABS and casing diameter in to fit, Dia in to sing height above land surface. 1 Steel 3 Stainless steel 5 Fiberglass A Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass A Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut CREEN-PERFORATED INTERVALS: From fit to fit, From fit to fit fit for fit	Application Number: EVATION: ft. 2
ANY X" IN SECTION BOX: Depth(s) Groundwater Encountered 1. WELL'S STATIC WATER LEVEL ft. below land Pump test data: Well water was ft. Bore Hole Diameter for DE USED AS: 5 Public water supply 1 Domestic 3 Feedlot 7 Lawn and garden only Was a chemical/bacteriological sample submitted to Department? mitted TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile 9 Other (specify be 2 PVC) 4 ABS To be a single height above land surface in, weight 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 1 Continuous slot 3 Mill slot 6 Wire wrapped 1 Continuous slot 4 Key punched 7 Torch cut REEN-PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 4 Key punched 7 Torch cut REEN-PERFORATED INTERVALS: From ft. to ft. From ft. From ft. From ft. From ft. From ft. To ft. From ft. From ft. To ft. From ft.	Application Number: EVATION: ft. 2
A State, ZIP Code COCATE WELL'S LOCATION WITH A DEPTH OF COMPLETED WELL. Depth(s) Groundwater Encountered 1. WELL'S STATIC WATER LEVEL	ft. 2
Depth(s) Groundwater Encountered 1	ff. 2
WELL'S STATIC WATER LEVEL ft. below land Pump test data: Well water was ft. below land Pump test data: Well water was ft. below land Pump test data: Well water was ft. below land ft.	surface measured on mo/day/yr
1 Domestic 3 Feedlot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden only was a chemical/bacteriological sample submitted to Department? mitted TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile 9 Other (specify be 2 PVC) 4 ABS 7 Fiberglass 1. In. to 1. In., weight above land surface 1. In., weight 1. Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS REEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 2 Louvered shutter 4 Key punched 7 Torch cut REEN-PERFORATED INTERVALS: From ft. to ft., From f	9 Dewatering 12 Other (Specify below) ly 10 Monitoring well ? Yes
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC) 4 ABS Thick casing diameter in. to ft., Dia in. The ft. to ft., Dia in. The ft. T	Water Well Disinfected? Yes No CASING JOINTS: Glued Clamped Pelow) Welded Threaded In to 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify) 15 From 16 to 17 From 18 to 19 From 10 Other (specify) 11 None (open hole) 12 From 13 None (open hole) 14 Other 15 To 16 To 17 To 18 To 19 To 10 To 10 To 11 None (open hole) 12 None (open hole) 13 None (open hole) 14 Other 15 To 16 To 17 To 18 To 19 To 10 To 10 To 11 None (open hole) 12 None (open hole) 13 To 14 Other 15 To 16 To 17 To 18 To 18 To 19 To 19 To 10 To 10 To 10 To 11 None (open hole) 12 To 13 To 14 Other 15 To 16 To 17 To 18 To 19 To 10 To 10 To 10 To 11 None (open hole) 11 None (open hole) 12 To 13 To 14 To 15 To 16 To 17 To 18 To 19 To 10 To 10 To 10 To 11 None (open hole) 11 None (open hole) 12 To 13 To 14 To 15 To 16 To 17 To 18 To 19 To 10 To 10 To 10 To 10 To 11 None (open hole) 11 None (open hole) 12 To 13 To 14 To 15 To 16 To 17 To 18 To 19 To 19 To 10 To 10 To 10 To 11 None (open hole) 11 None (open hole) 12 To 13 To 14 To 15 To 16 To 17 To 18 To 18 To 19 To 19 To 10 To 11 To 11 To 12 To 13 To 14 To 15 To 16 To 17 To 18 To 18 To 18 To 18 To 18
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be 2 PVC 4 ABS This casing diameter in to to the contamination: 1 Steel 3 RMP (SR) 7 Fiberglass This pecify be 2 Fiberglass This pecify be 3 Fiberglass This pecify be 4 ABS This pecify be 5 Fiberglass This pecify be 6 Asbestos-Cement 9 Other (specify be 6 PEC ABS) This pecify be 7 Fiberglass This pecify be 7 Fiberglass This pecify be 6 Asbestos-Cement 9 Other (specify be 6 PEC ABS) This pecify be 7 Fiberglass This pecify be 8 Fiberglass This pecify be 7 Fiberglass This pecify be 7 Fiber	Welded Threaded Threaded
2 PVC 4 ABS 7 Fiberglass nk casing diameter in. to ft., Dia in. to sing height above land surface in., weight in., weight per OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS REEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut REEN-PERFORATED INTERVALS: From ft. to ft., F From ft. to ft., F GRAVEL PACK INTERVALS: From ft. to ft., F GROUT MATERIAL: 1 Neat cement cout Intervals: From ft. to ft., F GROUT MATERIAL: 1 Neat cement cout Intervals: From ft. to ft., F GROUT MATERIAL: 1 Neat cement ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft	Threaded.
nk casing diameter in. to ft., Dia in. to sing height above land surface in., weight in.,	Ibs./ft. Vall thickness or gauge No 6.0 Solution 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify) From ft. to from ft. to from ft. to from ft. to
in height above land surface	10
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS REEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut REEN-PERFORATED INTERVALS: From ft. to ft., F From ft. to ft., F GRAVEL PACK INTERVALS: From ft. to ft., F From ft. to ft., F REOUT MATERIAL: 1 Neat cement cement grout 3 Bentonite 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fu	11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS REEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut REEN-PERFORATED INTERVALS: From ft. to ft., F From ft. to ft., F GRAVEL PACK INTERVALS: From ft. to ft., F GROUT MATERIAL: 1 Neat cement cout Intervals: From ft. to ft., F GROUT MATERIAL: 1 Neat cement cement grout 3 Bentonite cout Intervals: From ft. to ft., F GROUT MATERIAL: 1 Neat cement cement grout 3 Bentonite cout Intervals: From ft. to ft., F GROUT MATERIAL: 1 Neat cement grout 3 Bentonite cout Intervals: From ft. to ft., F GROUT MATERIAL: 1 Neat cement grout 7 Pit privy 11 Fu	12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify) From ft. to f From ft. to f From ft. to f 4 Other ft., From ft. to ft.
REEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 4 Key punched 7 Torch cut REEN-PERFORATED INTERVALS: From. ft. to ft., F From. ft. to ft., F GRAVEL PACK INTERVALS: From. ft. to ft., F From ft. to ft., F GROUT MATERIAL: 1 Neat cement grout 3 Bentonite ut Intervals: From. ft. to ft., F at is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fu	8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify) From ft. to From ft. to From ft. to From ft. to 4 Other ft. to ft. from ft. to ft. from ft. ft. ft.
1 Continuous slot 2 Louvered shutter 4 Key punched 7 Torch cut REEN-PERFORATED INTERVALS: From. ft. to ft., F From. ft. to ft., F GRAVEL PACK INTERVALS: From. ft. to ft., F From ft. to ft., F From ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. ft. ft. ft. ft. ft. ft. ft. ft. ft	9 Drilled holes 10 Other (specify) From ft. to f From ft. to f From ft. to f 4 Other ft., From ft. to ft. to ft.
2 Louvered shutter 4 Key punched 7 Torch cut REEN-PERFORATED INTERVALS: From. ft. to ft., F From ft. to ft., F GRAVEL PACK INTERVALS: From. ft. to ft., F From ft. to ft., F GROUT MATERIAL: 1 Neat cement Lut Intervals: From. ft. to ft., F Lut Intervals: F	10 Other (specify) From ft. to f From ft. to f From ft. to f Compared ft. to ft.
REEN-PERFORATED INTERVALS: From ft. to ft., F From ft. to ft., F GRAVEL PACK INTERVALS: From ft. to ft., F From ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. to ft., F at Intervals: From ft. to ft., F to ft., F The from ft. to ft., F GROUT MATERIAL: 1 Neat cement ft., From ft. to ft., F at Intervals: From ft. to ft., From ft	From ft. to f From ft. to f From ft. to f From ft. to f 4 Other f f ft., From ft. to f
From ft. to ft., F GRAVEL PACK INTERVALS: From ft. to ft., F From ft. to ft., F From ft. to ft., F GROUT MATERIAL: 1 Neat cement out Intervals: From ft. to ft., F at is the nearest source of possible contamination: 10 Liv 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fu	From ft. to f From ft. to f From ft. to f From ft. to f 4 Other ft. to f ft., From ft. to f
From ft. to ft., F GRAVEL PACK INTERVALS: From ft. to ft., F From ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. To ft. to ft., F GROUT MATERIAL: 1 Neat cement ft. To ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft. To ft., F GROUT MATERIAL: 1 Neat cement ft. To ft., F GROUT MATERIAL: 1 Neat cement ft., F GROUT MATERI	From ft. to f From ft. to f From ft. to f 4 Other ft. to f
at is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fu	ft., From ft. to
at is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fu	
2 Sewer lines 5 Cass pool 8 Soward larger 12 Ea	uel storage 15 Oil well/Gas well
2 device wiles 3 dess pool 6 dewaye layout 12 Fe	ertilizer storage 16 Other (specify below)
O Water Richard	secticide storage
	many feet? 350
OM TO LITHOLOGIC LOG FROM TO	PLUGGING INTERVALS
	7 EGGGING INTERVALE
12 Class	
40 fine a med SAM.	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) resolved on (1) constructed, (2) constructed, (3) constructed on (1) const	
er Well Contractor's License No. 3	
er the business name of by (signormal by the business name of by (signormal business name of by (signormal business name of b	gnature)