1 Loc		ATERWELL:	·	NE SW		VW	Section Number	Township Number	Range Number	
Distanc	Sedg	W1CK n frem nearest town or cit		1/4 SAE	1/4	1/4	7	T 26 s	R 1E E/W	
			•							
	<u>pprox</u> aterwell		& Merid:		10 VI	Sita 5	rd Add.	Wichita, Kansas	3	
	, ST. ADRESS		XANDER, I					Roard of Agricultur	e, Divivsion of Water Resource	
	Y, STATE, ZI		O Evansto hita,Kans					_		
_		LOCATION WITH	DEPTH OF		PRWEII	33	~ F1	Application Nu	nber:	
	X'' IN SECTION		Depth(s) grou			, 33 1	ft. El	LEVATION: 2 ft.	3 ft.	
t		<u> </u>	WELL'S STATI			_		Z 1t. BURFACE MEASURED ON mo/day/yi	- 144	
				C WATER p test data:	_	۲ Iwaterwas			10/12/13/2	
'	NW-	NE	Est. Yield			l water was i water was	ft.	after hours p		
_		X	Bore Hole Diame	gpm: ter 14		to 33	ft. ft.,	after hours p	. o er	
1Mile	*	E	WELL WATER		_	5 Public wat	-	-	n. to ft. 1 Injection well	
=			1 Domestic	3 Fee		6 Oil field w		_	2 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								(-1)		
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was									. mo/dav/vr sample was	
		S	submitted		•		-		s X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Ste	el	3 RMP (SR)			6 Asbestos-Cement 9 Other (Specify below)			below)	Welded	
2 PV	C	4 ABS		7 Flb	erglass	8	SDR-26		Threaded	
Blank c	asing Dian	neter 5	in. to 20	ft.,	, Dia	ir	ı. to	ft., Dia in	, to ft.	
Casing	height abo	ve land surface 1	2	in.,	weight	2.35	lbs. / ft.	Wall thickness or gauge No.	.214	
TYPE	OF SCRE	EN OR PERFORA	TION MATERIA				7 PVC	10 Asbestos-ce	ement	
1 Secti S Statistics Secti					5 Fiberglass 8 RMP (SR)			11 other (specify)		
2 Bra	ISS	4 Galvanized stee	el	6 Con	crete tile		9 ABS	12 None used	(open hole)	
SCRE	EN OR PE	RFORATION OPE	ENING ARE:		5 Gar	uzed wrapped		8 Saw cut	11 None (open hole)	
1 Cont	inous slot	3 Mill sl	ot		6 Wir	re wrapped		9 Drilled holes		
2 Louv	ered shutte	er 4 Key pı	unched		7 Tor	ch cut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 20						ft. to 27 ft., From			o ft.	
			from			ft. to	ft., Fro			
GRAVEL PACK INTERVALS: from 19				19	111, 2		ft., Fro		-	
			from		f	ft. to	ft., Fro			
6 GR	OUT MAT	ERIAL: 1 Neat	cement	2 Cement	grout	3 B	entonite	4 Other		
Grout Intervals: From 4 ft. to 19 ft., From ft. to ft., From ft. to									ft. to ft.	
		st source of possible			10 Liv				4 Abandon water well	
1 Septic tank 4 Lateral			al lines		7 Pit privy		11 Fuel :	- 1	5 Oil well/Gas well	
2 Sewer lines 5 Cess p			pool	8 Sewage lagoon		goon		lizer storage 1	16 Other (specify below)	
3 Wate	ertight sew	er lines 6 Seepa	age pit	9	9 Feedyard		13 Insec	ticide storage Nor	None Apparent	
	on form we		· · · · · · · · · · · · · · · · · · ·					How many feet?		
FROM	то 3		LITHOLOGIC L	<u>OG</u>		FROM	ТО	PLUGGING INT	ERVALS	
<u>0</u> 3	21	topsoil fine san								
<u>3</u> 21	22		la							
	32	clay medium s							· · · · · · · · · · · · · · · · · · ·	
44	5 2	Mediam 2	and				1			
	 						+ +			
	<u> </u>									
	 		-				1			
							1			
	-			-					HAIR CONTRACTOR OF THE CONTRAC	
								The state of the s	FRM	
			4.1.77							
	 		,			,				
	 	<u> </u>								
	—						1 1			
7										
CO	TRACTO	OR'S OR LANDOWNER	R'S CERTIFICATION:	This water	well was	(1) construc	ted, (2) reconst	ructed, or (3) plugged under	my jurisdiction and	
was co	ompleted	on (mo/day/year)		4.L.X.Z.Z.G	-4 18/-11 1	and this re	cord is true to t	the best of my knowledge ar mo/day/yr)11./.	nd belief. Kansas Water	
Under	the busin	rs Licelise No ness name of .Ha	rn Well	His vv.	ster well r	record was c	completed on (r	no/day/yr)	AMJ	