1 LOCATION OF WATER WELL:		FRACTION				Section Number	Township Number	Range Number	
		SW 1/4	NE	1/4	SW 1/4	7	r 26 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?									
6401 Campos Wichita, Kansas									
2 WATER WELL		DD HOMES			•••		****		
RR#, ST. ADRES							Board of Agriculture, D	Divivsion of Water Resource	
CITY, STATE, Z							Application Numbe	HT:	
	LOCATION WITH	DEPTH OF COM	APLETE	D WELL	45	ft. EL	EVATION:		
AN "X" IN SECTION	ON BOX:	Depth(s) groundw	ater Enco	ountered	1	ft.	2 ft.	3 ft.	
	WE	ELL'S STATIC W	ATER LI	EVEL 1	L7 F	FT. BELOW LAND SU	URFACE MEASURED ON mo/day/yr	07/24/1992	
NE Pump test			t data:	data: Well water was		ft.	after hours pum	nping gpm	
	1 1	Yield	gpm:	Well	l water was	ft.	after hours pum	nping gpm	
<u>u</u> w	1 1	e Hole Diameter	12	in.	to 45	ft.,	and in.	to ft.	
E Bote Hote Diameter WELL WATER TO BE							•		
SE Domestic 31				3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								
+	9	s a chemical/bacte	riological	l sample s	submitted to 1	-		no/day/yr sample was	
submitted Water Well Disinfected? Yes X No									
5 TYPE OF C.				ought iron		8 Concrete tile		Hued X Clamped	
	3 RMP (SR)			stos-Ceme		9 Other (Specify b	,	Velded	
2 PVC	4 ABS		7 Fiber	glass		SDR-26	1	Threaded	
Blank casing Dia		to 35	ft.,	Dia	_	n. to	ft., Dia in.	to ft.	
Casing height abo	ove land surface 12 EN OR PERFORATION	in., N Matediai		weight	2.29	lbs. / ft.	Wall thickness or gauge No. 10 Asbestos-ceme	.214	
1 Steel	3 Stainless Steel	(MATERIAL:	5 Fiberg	plass		7 PVC 8 RMP (SR)	11 other (specify		
2 Brass	4 Galvanized steel		6 Concr			9 ABS	12 None used (or	•	
	ERFORATION OPENING	CADE.	0.000		J		8 Saw cut	pen noie) 11 None (open hole)	
1 Continous slot		G ARE:			uzed wrapped re wrapped		9 Drilled holes	11 None (open note)	
2 Louvered shutt	5 Min slot	ed					10 Other (specify)		
1	ORATION INTERVALS			7 Torc		5 F	,		
SCREEN-LERI	JRAHON INTERVALS				nt. to 45	ft., Fron		ft.	
CRAY	TET DACK INTERVAL	from S: from 24		ft. to		ft., Fron		ft.	
GRAVEL PACK INTERVALS: from 24			1	ft. to 45 ft. to		ft., Fron ft., Fron		ft. ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonlte 4 Other									
Grout Intervals:		to 24		From		to	ft., From	ft. to ft.	
What is the nearest source of possible contamination:			,	14,110111		10 Livesto		Abandon water well	
1 Septic tank 4 Lateral lines			7 [7 Pit privy		11 Fuel st	L	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 S	8 Sewage lagoon			zer storage 16 (16 Other (specify below)	
12 Inscribilda stamas							Apparent		
Direction form w	ell?						How many feet?		
FROM TO	LITH	HOLOGIC LOG			FROM	1 TO	PLUGGING INTE	RVALS	
0 3	topsoil								
3 11	clay								
11 21	fine sand								
21 30	medium san	<u>d</u>							
30 33	clay								
33 45	medium san	<u>d</u>							
———									
							400		
⁷ CONTRACTO	OR'S OR LANDOWNER'S CE	RTIFICATION: Thi	s water v	vell was ((1) construc	ted, (2) reconstru	ucted, or (3) plugged under m	ny jurisdiction and	
was completed on (mo/day/year)									
Well Contracto	r's License No	Wall &	This Wate	er Well H	Record was	completed on (m	o/day/yr)	*1.74	
Under the pusi	ness name of		F		.#.\:\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	MM: by (sign	ature Jane Inc	derich	
Under the business name of Harp Well & Pump Service, Inc. by (signature) are The derich									