USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

| | | \mathbf{T} | |
|---|---|--------------|---------------------|
| | | | |
| T | R | EW | sec 1/4 1/4 1/4 No. |

Kansas State Dept. Of Health (Water Well Contractors) Forbes–Bldg. 740 Topeka, Kansas 66620

| | County | Township name | Fraction | | Section number | | | Town number | Range number | | |
|--|---------------------------|---------------------------------------|---|---|----------------|----|-------------------------|---|--|----------------|--|
| 1 Lacatian of well: | Sedgwick | Kechi NV | / NW l NW | 1 | | 8 | | 268 | 1E | | |
| Distance and direction from nearest town or city 6944 North Seneca Street address of well location if in city: Wichita, Kansas Address: Bud Coons 6944 North Seneca | | | | | | | | | | | |
| Lacate with "X" in section below: Sketch map: | | | | | | | 4 We | II depth:ft. D | ate of completion 7-1 | 4-75 | |
| X | | | | | | · | | Cable tool Rotary Hollow rad Jetted Domestic Public | Bored Reverse rotary supply Industry | 1 | |
| W | | | | | | | | ing: Material VPCT | urface <u>12</u> in. | | |
| | S Mile | | | | | | _ | 5 in. to50ft. depth D | /eight lbs./ft rive shoe? [] Yes [] No | | |
| 2 | Тур | e and color of material | | | From | То | 0 5 | een: | wan Dlastic | 1 | |
| Top Soil and Clay | | | | | 0 | 20 | Tvi | inufacturer Sunflow De styrene D | ia. 5 [#] | | |
| Fine Sand | | | | | 20 | 35 | Set | between 35 ft. and tings: | 50 ft | | |
| Coarse S | Coarse Sand | | | | | 47 | Gr | avel pack 🔼 Yes 🗌 No S | Size range of material | 1/8# | |
| Clay | | · · · · · · · · · · · · · · · · · · · | *************************************** | , | 47 | 50 | 9 Sta | tic water level: 18 ft. below land surface | Date 7-14-75 | <u>;</u> | |
| | | | | | | | _ | mping level below land surf —— ft. after —— hrs. —— ft. after —— hrs. | pumping g.p.m. pumping g.p.m. | | |
| | | | | | | | 11 Wa | mated maximum yield —— ter sample submitted: Yes No Date | · |] | |
| | | | | | | | | II head completion: Pitless adapter 12 | Inches above grade | 1 | |
| | | | | | | | X | Il grouted? X Yes Neat cement Bentonit oth: From t. to | 10 ft. | | |
| | | | | | | | ft. | arest source of possible con 150 Direction N | Type <u>tan</u> | | |
| | | | | | | | 15 Pur Mo | np: | Not installed | | |
| | | | | | | | Ler | del number H ngth of drop pipe ft | | | |
| | | | · · · | | | | _ | _ | Turbine | | |
| | (use | a second sheet if needed) | | | | | | Certrifugal | Other | _ | |
| 16 Remarks: elevati Topography: Hill Slope | ∘∘ Flat G _r oı | and | | | | | Thi rep Hi Bus | ter well contractor's certifications well was drilled under my ort is true to the best of my well & iness name chita. | jurisdiction and this knowledge and belief. Pump 236 License No. Kansas | 7209 | |
| Upland Valley | | | | | | | Sig | Authorized represer | Date 7-7 | η - <i>J</i> Ξ | |

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5