

1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 NW 1/4 Section Number 18 Township Number T 26 S Range Number R 10 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? See below

2 WATER WELL OWNER: Paul Fruend
 RR#, St. Address, Box #: 2119 Ventosa
 City, State, ZIP Code: Valley Center Kansas 67147
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 34 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 19 ft. 2. 19 ft. 3. 19 ft.
 WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 19 ft. after 19 hours pumping 19 gpm
 Est. Yield 19 gpm: Well water was 19 ft. after 19 hours pumping 19 gpm
 Bore Hole Diameter 19 in. to 19 ft., and 19 in. to 19 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR)
☒ 2 PVC ☐ 4 ABS
 Blank casing diameter 5 in. to 28 ft., Dia 28 in. to 28 ft., Dia 28 in. to 28 ft., Dia 28 in. to 28 ft.
 Casing height above land surface 12 in., weight 28 lbs./ft. Wall thickness or gauge No. 160PVC
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 RVC ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 28 ft. to 34 ft., From 28 ft. to 34 ft., From 28 ft. to 34 ft., From 28 ft. to 34 ft.
 GRAVEL PACK INTERVALS: From 19 ft. to 34 ft., From 19 ft. to 34 ft., From 19 ft. to 34 ft., From 19 ft. to 34 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 19 ft., From 3 ft. to 19 ft., From 3 ft. to 19 ft., From 3 ft. to 19 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? West How many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	12	clay			
12	34	fine to med sand			

7 CONTRACTOR'S OR LANDOWNERS CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-8-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 12-8-92 under the business name of Weninger Drilling Inc. by (signature) Susan H. Weninger