1 LOCATION OF WATER WELL:		FRACTION			Section Number	Township Number	Range Number	
Sedgy			CW	C19	1	1	1	
	VICK frem nearest town or city str	SE 1/4	SW 1/4	SE 1/4	18	_ т 26 s	R 1E E/W	
	•		•					
2 WATER WELL		<u>Vichita, Ka</u>	insas					
RR#, ST. ADRESS,	COLLIN	AN, Kent				Roard of A priculty	ure, Divivsion of Water Resource	
CITY STATE SINGERS STATE AND A STATE OF								
3 LOCATE WELL'S I		DEPTH OF COM		40	a FIF	Application N	umber:	
AN "X" IN SECTIO		Depth(s) groundwa			ft. ELE	VATION:	3 ft.	
1	<u> </u>					2 ft. FACE MEASURED ON mo/day/		
	"	ELL'S STATIC W. Pump test		15 FI Il water was		•		
NW		t. Yield					pumping gpm	
		re Hole Diameter		ll water was			pumping gpm	
1Mile	1 1	TE HOLE DIMMETER ELL WATER TO E		to 40 5 Public wate	ft.,	and 8 Air conditioning	in. to ft. 11 Injection well	
	"	1 Domestic	3 Feedlot	6 Oil field wa	•••		12 Other (Specify below)	
SW-	SE	2 Irrigation	4 Industrial	7 Lawn and g		0 Monitoring well		
	X w	as a chemical/bacte	riological sample	•		•	es, mo/day/yr sample was	
	e e	ubmitted	i iologicai sample	sublificted to D	-		es X No	
5 TYPE OF CA			5 Wrought inc		Concrete tile	CASING JOINTS:	Glued X Clamped	
1 Steel	3 RMP (SR)		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (Speci					
2 PVC	4 ABS		7 Fiberglass		DR-26	2011)	Threaded	
Blank casing Diam		. to 30	ft., Dia	in.		ft., Dia i	in. to ft.	
Casing height above	_	12 in.,	welght	2.29	• • • • • • • • • • • • • • • • • • • •	Vall thickness or gauge No.		
	N OR PERFORATIO		weight		7 PVC	10 Asbestos-		
1 Steel	3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (spe	ecify)	
2 Brass	4 Galvanized steel		6 Concrete tile	9	ABS	12 None used	d (open hole)	
SCREEN OR PER	REFORATION OPENI	NG ARE:	5 Ga	uzed wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot	3 Mill slot		6 Wire wrapped			9 Drilled holes		
2 Louvered shutte		hed		rch cut		10 Other (specify)		
SCREEN-PERFO	RATION INTERVAL			ft. to 40	6 F	•	to ft.	
	CTION IN DRVAL	20 30			ft., From			
CDAVI	EL PACK INTERVAI	from LS: from 24		ft. to ft. to 40	ft., From		to ft.	
GRAVI	EL FACK INTERVAL	rom 24 from		ft. to	ft., From ft., From		to ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals:		t. to 24	ft., From				a	
What is the nearest source of possible contamination			ft., From ft. to		10 Livestoc	ft., From ek pens	ft. to ft. 14 Abandon water well	
1 Septic tank	4 Lateral li				11 Fuel sto		15 Oil well/Gas well	
2 Sewer lines	5 Cess poo	ol .	8 Sewage lagoon		12 Fertiliz		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								
Direction form wel			•			How many feet? 50		
FROM TO	LIT	HOLOGIC LOG	IC LOG FROM TO		то	PLUGGING INTERVALS		
0 3	topsoil	110 P						
3 7	clay							
7 21	fine sand							
21 40	medium sar	nd						
	• • • • • • • • • • • • • • • • • • • •				1			
	-							
l								
<u> </u>					_			
								
 								
 					+			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
						/day/yr)	12	
Under the busin	ess name ofHAX]	h	c.ump		by (signa	ture) Jano 1. H	nederick	
25								