


1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 SW 1/4 Section Number 18 Township Number T 26 S Range Number R 1 E  
 County: Sedgewick  
 Distance and direction from nearest town or city street address of well if located within city?

See Below.

2 WATER WELL OWNER: Gertrude Stine  
 RR#, St. Address, Box #: 5601 N. Legion  
 City, State, ZIP Code: Wichita KS 67214  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 18 ft. below land surface measured on 3-17-90  
 Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 20 ft.  
 WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on 3-17-90  
 Pump test data: Well water was 18 ft. after 1/2 hours pumping 20 gpm  
 Est. Yield 70 gpm: Well water was 18 ft. after 1/2 hours pumping 20 gpm  
 Bore Hole Diameter: 1 1/2 in. to 40 ft., and 40 in. to 40 ft.  
 WELL WATER TO BE USED AS:  
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well  
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:  
☐ 1 Steel ☒ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued X Clamped X  
☐ 2 PVC ☒ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded X  
☐ 7 Fiberglass Threaded X  
 Blank casing diameter 5 in. to 30 ft., Dia. 1 1/2 in. to 40 ft., Dia. 1 1/2 in. to 40 ft., Dia. 1 1/2 in. to 40 ft.  
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR-26  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement  
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☒ 8 RMP (SR) ☐ 11 Other (specify)  
☐ 9 ABS ☐ 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)  
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes  
☐ 7 Torch cut ☐ 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From 30 ft. to 40 ft., From 30 ft. to 40 ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 40 ft., From 20 ft. to 40 ft., From 20 ft. to 40 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other  
 Grout Intervals: From 3 ft. to 20 ft., From 3 ft. to 20 ft., From 3 ft. to 20 ft.  
 What is the nearest source of possible contamination:  
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well  
☒ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well  
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)  
☐ 13 Insecticide storage  
 Direction from well? Noeth. How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	16	Clay			
16	29	fine sand.			
29	30	clay			
30	40	gravel.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-17-90 and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 3-24-90  
 under the business name of Weninger Drilling by (signature) Weninger