


1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW 1/4 NE 1/4 NW 1/4	Section Number 18	Township Number T 26 S	Range Number R 1E EW
Distance and direction from nearest town or city street address of well if located within city? 6110 Calma Wichita, Ks.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Rose Martin 6110 Calma Wichita, Ks.			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		Board of Agriculture, Division of Water Resources Application Number:			
<div style="text-align: center;"></div>		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 13 ft.			
		Depth(s) Groundwater Encountered 1. 13 ft. 2. 13 ft. 3. 13 ft. WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 8-2-89 Pump test data: Well water was 11 in. to 40 ft. after 1 hours pumping 11 gpm Est. Yield 11 gpm: Well water was 11 ft. after 1 hours pumping 11 gpm Bore Hole Diameter 11 in. to 40 ft. and 11 in. to 40 ft. WELL WATER TO BE USED AS: 1 <u>Domestic</u> 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 <u>RMP (SR)</u> 2 PVC 4 <u>ABS</u>		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 6 Asbestos-Cement 9 Other (specify below) Welded X 7 Fiberglass <u>Cer-Mac styrene SDR-26</u> Threaded X			
Blank casing diameter 5 in. to 30 ft. Dia. 5 in. to 30 ft. Dia. 5 in. to 30 ft.		Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. .203			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 <u>RMP (SR)</u> 2 Brass 4 Galvanized steel 6 Concrete tile 9 <u>ABS</u>		10 Asbestos-cement 11 Other (specify) X 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 <u>Saw cut</u> 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		10 Other (specify) X 11 None (open hole)			
SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft. From 30 ft. to 40 ft.		GRAVEL PACK INTERVALS: From 24 ft. to 40 ft. From 24 ft. to 40 ft.			
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other		Grout Intervals: From 4 ft. to 24 ft. From 4 ft. to 24 ft. From 4 ft. to 24 ft.			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage		Direction from well? East How many feet? 100			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			
3	11	clay			
11	23	fine sand			
23	40	medium sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-2-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10-16-89 under the business name of Harp Well and Pump Service, Inc. by (signature) <i>Mary Arnold</i>					