


1 LOCATION OF WATER WELL: Fraction SE 1/4 NW 1/4 NW 1/4 Section Number 18 Township Number T 26 S Range Number R 10 E  
 County: Edgar  
 Distance and direction from nearest town or city street address of well if located within city: SEE BELOW

2 WATER WELL OWNER: RON PHILLIPS  
 RR#, St. Address, Box #: 2226 UENTOSA  
 City, State, ZIP Code: WICHITA, KS 67204  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 42 ft. ELEVATION: 5-1-90  
 Depth(s) Groundwater Encountered 1. 21 ft. 2. 21 ft. 3. 20 ft.  
 WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was 21 ft. after 12 hours pumping 20 gpm  
 Est. Yield 70 gpm: Well water was 21 ft. after 12 hours pumping 20 gpm  
 Bore Hole Diameter 11 in. to 42 ft., and 42 in. to 42 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
☒ 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
☒ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X  
☒ 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X  
☒ 2 PVC 4 ABS 7 Fiberglass Threaded X  
 Blank casing diameter 5 in. to 30 ft., Dia. 30 in. to 42 ft., Dia. 42 in. to 42 ft.  
 Casing height above land surface 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. SDR-26  
 TYPE OF SCREEN OR PERFORATION MATERIAL: ☒ 7 PVC 10 Asbestos-cement  
☒ 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
☒ 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
☒ 1 Continuous slot ☒ 3 Mill slot 6 Wire wrapped 9 Drilled holes  
☒ 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 42 ft., From 30 ft. to 42 ft., From 30 ft. to 42 ft.  
 GRAVEL PACK INTERVALS: From 22 ft. to 42 ft., From 22 ft. to 42 ft., From 22 ft. to 42 ft.

6 GROUT MATERIAL: 1 Neat cement ☒ 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 3 ft. to 22 ft., From 3 ft. to 22 ft., From 3 ft. to 22 ft., From 3 ft. to 22 ft.  
 What is the nearest source of possible contamination: ☒ 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
☒ 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
☒ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 Direction from well? North How many feet? 90

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	12	clay			
12	29	fine sand			
29	30	clay			
30	42	gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-1-90 and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-3-90  
 under the business name of Weninger Pully by (signature) Weninger