


1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 NE 1/4 Section Number 18 Township Number T 26 S Range Number R 1 EW
 County: SEDGWICK
 Distance and direction from nearest town or city street address of well if located within city?

1505 W. 61st Rd. - WICHITA

2 WATER WELL OWNER: WELENGER DRILLING Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 1505 W. 61st Rd. Application Number:
 City, State, ZIP Code: WICHITA, KS, 67204

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 316 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 18 ft. 2. . ft. 3. . ft.
 WELL'S STATIC WATER LEVEL: 18 ft. below land surface measured on mo/day/yr 11-20-87
 Pump test data: Well water was . ft. after . hours pumping . gpm
 Est. Yield 50 gpm: Well water was . ft. after . hours pumping . gpm
 Bore Hole Diameter: 11 in. to 36 in. to . ft. and . in. to . ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR)
 2 PVC 4 ABS
 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped .
 6 Asbestos-Cement 9 Other (specify below) Welded .
 7 Fiberglass Threaded.
 Blank casing diameter: 5 in. to 36 in. Dia. . in. to . ft. Dia. . in. to . ft.
 Casing height above land surface: 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. SPR-26

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) .
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot
 2 Louvered shutter 4 Key punched
 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) .

SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft. From . ft. to . ft.
 From . ft. to . ft. From . ft. to . ft.
 GRAVEL PACK INTERVALS: From 18 ft. to 36 ft. From . ft. to . ft.
 From . ft. to . ft. From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 18 ft. From . ft. to . ft. From . ft. to . ft. From . ft. to . ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? North How many feet? 175

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	top soil			
2	11	clay			
11	22	fine sand			
22	23	clay			
23	36	gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Nov. 20, 1987 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318,184 This Water Well Record was completed on (mo/day/year) Nov. 20, 1987 under the business name of WELENGER DRILLING by (signature) James We Wenger