			WAT	TER WELL RECORD	orm WWC-5	KSA 82			
4	ON OF WAT		Fraction	CD CT	1	tion Number	200		Range Number
	Sedgwic			1/4 SE 1/4 SW		18	т 26	s	R 1 E EW
			•	address of well if located	within city?				
466 N	<u>. Charle</u>	s, Wichita	a, KS.	MaCaulou					
			& Phyllis	мссаитеу					
RR#, St.	Address, Box		N. Charles	5			Board of A	griculture, Di	vision of Water Resource
City, State	, ZIP Code	Wichi	ta, KS.				Application		
LOCAT	E WELL'S LO	CATION WITH	4 DEPTH OF	COMPLETED WELL. 40)	ft. ELEVA	ATION:		
AN A	IN SECTION	BUX:	Depth(s) Groun	ndwater Encountered 1.	16	ft.	2	ft. 3.	
iΓ	!	1	WELL'S STAT	IC WATER LEVEL 16	ft. b	elow land su	rface measured on	mo/day/yr	4-16-87
	NW I	NE	Pu	mp test data: Well water	was	ft. a	after	hours pur	ping gpm
	- ,,,,,	1,46	Est. Yield	gpm: Well water	was	ft. a	after	hours pur	ping gpm
• w -	i		Bore Hole Dia	meter $\dots 11\dots$ in \dots to \dots			and	in.	to
* *	! [1] 6	WELL WATER			r supply			njection well
ī l	cw	!	1 Domesti	c 3 Feedlot 6	Oil field wa	ter supply	9 Dewatering	12 O	ther (Specify below)
l l	3w	3:	2 Irrigation	4 Industrial 7	Lawn and	garden only	10 Observation wel	ı	
	k i		Was a chemica	al/bacteriological sample su	ubmitted to D	epartment? Y	esNoX	; If yes, r	mo/day/yr sample was sub
	S		mitted			Wa	ater Well Disinfected	? Yes X	No
TYPE	OF BLANK C	ASING USED:		5 Wrought iron	8 Concre	ete tile	CASING JOIN	NTS: Glued	XClamped
1 St	ee l	3 RMP (S	SR)	6 Asbestos-Cement	9 Other	(specify belo	w)		d
2 P\		4 ABS	_	7 Fiberglass	Cer-M	ac Styre	ne - SDR-26	Thread	led
3lank casi	ng diameter .	5	.in. to 25 .	ft., Dia	in. to		ft., Dia	in	ı. to ft.
Casing he	ight above la	nd surface.12.		in., weight	• <u>5</u> 9	lbs.	ft. Wall thickness o	r gauge No.	. • 203
YPE OF	SCREEN OF	PERFORATIO	N MATERIAL:		7 PV	С	10 Asbe	stos-cemen	t
1 St	eel	3 Stainles	s steel	5 Fiberglass	8 RM	IP (SR)	11 Othe	r (specify) .	
2 Br	ass	4 Galvania	zed steel	6 Concrete tile	9 AB	S	12 None	used (ope	n hole)
CREEN	OR PERFOR	ATION OPENIN	IGS ARE:	5 Gauze	d wrapped		8 Saw cut		11 None (open hole)
1 Cc	entinuous slot	3 M	Aill slot	6 Wire w	rapped		9 Drilled holes		
2 Lo	uvered shutte	r 4 K	ey punched	7 Torch					
SCREEN-	PERFORATE	D INTERVALS:	From	25 ft. to	40	ft., Fro	m	ft. to	
				ft. to					
(GRAVEL PAC	K INTERVALS:	From	14 ft. to	40	ft., Fro	m	ft. to	
+			From	ft. to		ft., Fro	m	ft. to	ft.
GROUT	MATERIAL:			2 Cement grout					
Grout Inte				ft., From	ft.	to <i>.</i>	ft., From		. ft. to
		rce of possible	contamination:			10 Lives	tock pens	14 Aba	andoned water well
	1 Septic tank 4 Lateral lines			7 Pit privy	11 Fuel storage		storage	15 Oil	well/Gas well
2 Sewer lines 5 Cess pool			8 Sewage lagor	on 12 Fertilizer storage		izer storage	16 Oth	er (specify below)	
	_	r lines 6 Seep	page pit	9 Feedyard		13 Insec	ticide storage		
	rom well? E	<u>last</u>				How ma	ny feet? 71	****	
FROM	то		LITHOLOGIC	LOG	FROM	ТО	L	ITHOLOGIC	LOG
0	3	Tops			1				
3	12	Clay							
12	24		Sand						
24	40	Medi	um Sand						
	-								
CONTE	RACTOR'S O	R LANDOWNE	R'S CERTIFICA	TION: This water well was	(1) constru	cted. (2) reco	enstructed, or (3) plu	laged under	r my jurisdiction and was
				This Water We				<u> </u>	-20-87
	business nam			Ump Service, Inc			ture) Mana	(In mi	01
INSTRUC	TIONS: Use tvo	ewriter or ball poin	nt pen. PLEASE PR	ESS FIRMLY and PRINT clear	y. Please fill in I	olanks, underlin	e or circle the correct	nswers. Send	top three copies to Kansas
Departme	nt of Health and	Environment, Bu	reau of Water Prote	ection, Topeka, Kansas 66620-	7320, Telephor	e: 913-862-936	60. Send one to WAT	R WELL OWN	ER and retain one for your
records.									