

1 LOCATION OF WATER WELL: County: Sedg. Fraction: NW 1/4 SE 1/4 SW 1/4 Section Number: 18 Township Number: T 26 S Range Number: R 10 E  
Distance and direction from nearest town or city street address of well if located within city? SS03 No Chalks Wichita KS

2 WATER WELL OWNER: LEEWOOD HOMES  
RR#, St. Address, Box #: 6130 LEGION  
City, State, ZIP Code: Wichita KS 67204  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

4 DEPTH OF COMPLETED WELL: 42 ft. ELEVATION: 1818 ft. below land surface measured on mo/day/yr 6-30-81  
Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 18 ft.  
WELL'S STATIC WATER LEVEL 1818 ft. below land surface measured on mo/day/yr 6-30-81  
Pump test data: Well water was 18 ft. after 2 hours pumping 20 gpm  
Est. Yield 50 gpm: Well water was 18 ft. after 2 hours pumping 20 gpm  
Bore Hole Diameter 11 in. to 42 ft., and 42 in. to 42 ft.  
WELL WATER TO BE USED AS:  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X  
Blank casing diameter 5 in. to 35 ft., Dia 5 in. to 35 ft., Dia 5 in. to 35 ft.  
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No 50R-26  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
SCREEN-PERFORATED INTERVALS: From 35 ft. to 42 ft., From 35 ft. to 42 ft., From 35 ft. to 42 ft.  
GRAVEL PACK INTERVALS: From 15 ft. to 42 ft., From 15 ft. to 42 ft., From 15 ft. to 42 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout intervals: From 5 ft. to 15 ft., From 15 ft. to 42 ft., From 15 ft. to 42 ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
Direction from well? West How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	12	Red clay.			
12	30	Fine sand.			
30	31	Red clay.			
31	42	Course GRADE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-30-81 and this record is true to the best of my knowledge and belief. Kansas  
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-2-81  
under the business name of Wenger Paving by (signature) James Wenger  
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

26

R

1

EW

SEC.

18

NW 1/4

SE 1/4

SW 1/4

NE 1/4