


USE TYPEWRITER OR BALL  
POINT PEN-PRESS FIRMLY,  
PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and  
Environment-Division of Environment  
(Water well Contractors)  
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
		SEDGWICK	NE 1/4 NW 1/4 NE	18	T 26 S R 1	EN
2. Distance and direction from nearest town or city:		3. Owner of well:		67204		
Street address of well location if in city:		R.R. or street:		WICHITA, KANS		
1601 W 61ST N,		1601 W 61N		67204		
WICHITA, KS		City, state, zip code:		WICHITA, KANS 67204		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 9 in. Completion date 3-11-80		
N		DRILLED 9" HOLE TO 12' - THEN 6" HOLE TO 3' STATIC WATER AT 18' - INSTALLED CASING + USED SAND BUCKET TO COMPAETE		Well depth 42 ft. GRADE		
				7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary		
1 Mile				8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lown Oil field water Other		
S				9. Casing: Material RMP Height: Above or below Threading Welded Surface 12 in. Dia. 5 in. to 43 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 200		
1 Mile				10. Screen: Manufacturer's name CER-MAC Type RMP Dia. 5 INCH Slot/gauze 0.31 Length 42 Set between 32 ft. and 42 ft. Gravel pack? NO Size range of material		
5. Type and color of material		From To		11. Static water level: 18 ft. below land surface Date 3/1/80		
TOP SOIL - SANDY BLACK		0 3		12. Pumping level below land surfaces: 18 ft. after hrs. pumping NA g.p.m. 18 ft. after hrs. pumping NA g.p.m. Estimated maximum yield 100 g.p.m.		
SANDY SOIL TAN		3 7		13. Water sample submitted: Yes X No Date		
SAND FINE TAN		7 12		14. Well head completion: Pitless adapter 12 inches above grade		
SANDY CLAY GRAY		12 16		15. Well grouted? YES With: Neat cement Bentonite X Concrete Depth: From 2 ft. to 12 ft.		
SAND COARSE GRAY		16 18		16. Nearest source of possible contamination 75 ft. Direction N Type SEWER Well disinfected upon completion? Yes X No		
SAND TAN MED		18 30		17. Pump: Not installed Manufacturer's name 10 HP 230 Volts Length of drop pipe 30 ft. capacity 28 g.p.m. Type: Submersible Turbine Jet Reciprocating Centrifugal Other		
SAND COARSE TAN		30 42				
(Use a second sheet if needed)						
18. Elevation: 1300		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN/UMAWELL Business name 3142 MENARD, WICHITA License No. 104 Address 3142 MENARD, WICHITA Signed 4/8/80 Date 4/8/80		
Topography: Hill Slope Upland Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5