


1 LOCATION OF WATER WELL:
County: Sedgwick
Distance and direction from nearest town or city street address of well if located within city?
5002 Irving Wichita Ks.

Fraction: 1/4
Section Number: 21
Township Number: T 26 S
Range Number: R 1 E

2 WATER WELL OWNER:
RR#, St. Address, Box # :
City, State, ZIP Code

D. L. Cole
5002 Irving
Wichita Ks. 67204

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION: 4-5-88 ft.
Depth(s) Groundwater Encountered 1. 16 ft. 2. 16 ft. 3. 16 ft.
WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 16 ft. after 2 hours pumping 20 gpm
Est. Yield 75 gpm: Well water was 16 ft. after 2 hours pumping 20 gpm
Bore Hole Diameter 11 in. to 38 ft., and 38 in. to 38 ft.
WELL WATER TO BE USED AS:
☒ Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR)
2 PVC 4 ABS
Blank casing diameter 5 in. to 28 ft., Dia. 12 in. to 1.59 lbs./ft. Wall thickness or gauge No. SDR26
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR26
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
28 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 16 ft. to 38 ft., From 16 ft. to 38 ft., From 16 ft. to 38 ft., From 16 ft. to 38 ft.
GRAVEL PACK INTERVALS: From 16 ft. to 38 ft., From 16 ft. to 38 ft., From 16 ft. to 38 ft., From 16 ft. to 38 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 16 ft., From 16 ft. to 38 ft., From 16 ft. to 38 ft., From 16 ft. to 38 ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? EAST How many feet? 80

FROM TO LITHOLOGIC LOG

0 2 top so.

2 12 clay.

12 38 fine to med sand.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-5-88 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/year) 6-29-88
under the business name of Weninger Drilling by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EWM
SEC.
1/4
1/4
1/4